

Package ‘NonCompart’

January 20, 2025

Version 0.7.0

Date 2023-11-15

Title Noncompartmental Analysis for Pharmacokinetic Data

Description Conduct a noncompartmental analysis with industrial strength.

Some features are

- 1) Use of CDISC SDTM terms
- 2) Automatic or manual slope selection
- 3) Supporting both 'linear-up linear-down' and 'linear-up log-down' method
- 4) Interval(partial) AUCs with 'linear' or 'log' interpolation method

* Reference: Gabrielsson J, Weiner D. Pharmacokinetic and Pharmacodynamic Data Analysis - Concepts and Applications. 5th ed. 2016. (ISBN:9198299107).

Author Kyun-Seop Bae [aut]

Maintainer Kyun-Seop Bae <k@acr.kr>

Copyright 2016-, Kyun-Seop Bae

License GPL-3

NeedsCompilation no

LazyLoad yes

Repository CRAN

URL <https://cran.r-project.org/package=NonCompart>

Date/Publication 2023-11-15 05:50:02 UTC

Contents

NonCompart-package	2
AUC	3
BestSlope	4
DetSlope	5
gAUC	6
gIntAUC	8
gInterpol	9
IntAUC	10

Interpol	11
LinAUC	12
LogAUC	13
Slope	14
sNCA	15
tblAUC	18
tblINCA	19
Unit	20
UnitUrine	21

Index	23
--------------	-----------

NonCompart-package *Noncompartmental Analysis for Pharmacokinetic Data*

Description

It conducts a noncompartmental analysis(NCA) with industrial strength.

Details

The main functions are

tblINCA to perform NCA for many subjects.

sNCA to perform NCA for one subject.

Author(s)

Kyun-Seop Bae <k@acr.kr>

References

1. Gabrielsson J, Weiner D. Pharmacokinetic and Pharmacodynamic Data Analysis - Concepts and Applications. 5th ed. 2016.
2. Shargel L, Yu A. Applied Biopharmaceutics and Pharmacokinetics. 7th ed. 2015.
3. Rowland M, Tozer TN. Clinical Pharmacokinetics and Pharmacodynamics - Concepts and Applications. 4th ed. 2011.
4. Gibaldi M, Perrier D. Pharmacokinetics. 2nd ed. revised and expanded. 1982.

Examples

```
# Theoph and Indometh data: dose in mg, conc in mg/L, time in h
tblINCA(Theoph, key="Subject", colTime="Time", colConc="conc", dose=320,
          adm="Extravascular", doseUnit="mg", concUnit="mg/L")

tblINCA(Indometh, key="Subject", colTime="time", colConc="conc", dose=25,
          adm="Infusion", dur=0.5, doseUnit="mg", concUnit="mg/L", R2ADJ=0.9)
```

```
# For individual NCA
iAUC = data.frame(Name=c("AUC[0-12h]", "AUC[0-24h]"), Start=c(0,0), End=c(12,24)) ; iAUC

x = Theoph[Theoph$Subject=="1", "Time"]
y = Theoph[Theoph$Subject=="1", "conc"]

sNCA(x, y, dose=320, doseUnit="mg", concUnit="mg/L", timeUnit="h", iAUC=iAUC)
sNCA(x, y, dose=320, concUnit="mg/L", iAUC=iAUC)
```

AUC

Calculate Area Under the Curve (AUC) and Area Under the first Moment Curve (AUMC) in a table format

Description

Calculate Area Under the Curve(AUC) and the first Moment Curve(AUMC) in two ways; 'linear trapezoidal method' or 'linear-up and log-down' method. Return a table of cumulative values.

Usage

```
AUC(x, y, down = "Linear")
```

Arguments

x	vector values of independent variable, usually time
y	vector values of dependent variable, usually concentration
down	either of "Linear" or "Log" to indicate the way to calculate AUC and AUMC

Details

down="Linear" means linear trapezoidal rule with linear interpolation. down="Log" means linear-up and log-down method.

Value

Table with two columns, AUC and AUMC; the first column values are cumulative AUCs and the second column values cumulative AUMCs.

Author(s)

Kyun-Seop Bae <k@acr.kr>

References

Rowland M, Tozer TN. Clinical Pharmacokinetics and Pharmacodynamics - Concepts and Applications. 4th ed. pp687-689. 2011.

See Also

[LinAUC](#), [LogAUC](#)

Examples

```
AUC(Theoph[Theoph$Subject==1, "Time"], Theoph[Theoph$Subject==1, "conc"])
AUC(Theoph[Theoph$Subject==1, "Time"], Theoph[Theoph$Subject==1, "conc"], down="Log")
```

BestSlope

Choose the best-fit slope for the log(y) and x regression by the criteria of adjusted R-square.

Description

It sequentially fits ($\log(y) \sim x$) from the last point of x to the previous points with at least 3 points. It chooses a slope the highest adjusted R-square. If the difference is less then 1e-4, it pickes longer slope.

Usage

```
BestSlope(x, y, adm = "Extravascular", TOL=1e-4, excludeDelta = 1)
```

Arguments

x	vector values of x-axis, usually time
y	vector values of y-axis, usually concentration
adm	one of "Bolus" or "Infusion" or "Extravascular" to indicate drug administration mode
TOL	tolerance. See Phoenix WinNonlin 6.4 User's Guide p33 for the detail.
excludeDelta	Improvement of R2ADJ larger than this value could exclude the last point. Default value 1 is for the compatibility with other software.

Details

Choosing the best terminal slope (y in log scale) in pharmacokinetic analysis is somewhat challenging, and it could vary by analysis performer. Phoenix WinNonlin chooses a slope with highest adjusted R-squared and the longest one. The difference of adjusted R-Squared less than TOL considered to be 0. This function uses ordinary least square method (OLS). Author recommends to use `excludeDelta` option with about 0.3.

Value

R2	R-squared
R2ADJ	adjusted R-squared
LAMZNPT	number of points used for slope
LAMZ	negative of the slope, lambda_z
b0	intercept of the regression line
CORRXY	correlation of log(y) and x
LAMZLL	earliest x for lambda_z
LAMZUL	last x for lambda_z
CLSTP	predicted y value at the last point, predicted concentration for the last time point

Author(s)

Kyun-Seop Bae <k@acr.kr>

See Also

[Slope](#)

Examples

```
BestSlope(Theoph[Theoph$Subject==1, "Time"], Theoph[Theoph$Subject==1, "conc"])
BestSlope(Indometh[Indometh$Subject==1, "time"], Indometh[Indometh$Subject==1, "conc"],
          adm="Bolus")
```

DetSlope

Determine slope for the log(y) and x regression manually

Description

You choose a slope for terminal half-life.

Usage

```
DetSlope(x, y, SubTitle="", sel.1=0, sel.2=0)
```

Arguments

x	vector values of x-axis, usually time
y	vector values of y-axis, usually concentration
SubTitle	subtitle to be shown on the plot
sel.1	default index of the first element to use
sel.2	default index of the last element to use

Details

Sometimes BestSlope cannot find terminal slope satisfactorily. Then you can use this function to choose manually. It returns the same format result with BestSlope with an attribute indicating used points.

Value

R2	R-squared
R2ADJ	adjusted R-squared
LAMZNPT	number of points used for the slope
LAMZ	negative of the slope, lambda_z
b0	intercept of the regression line
CORRXY	correlation of log(y) and x
LAMZLL	earliest x for lambda_z
LAMZUL	last x for lambda_z
CLSTP	predicted y value at the last point, predicted concentration for the last time point

Author(s)

Kyun-Seop Bae <k@acr.kr>

See Also

[Slope](#)

Examples

```
DetSlope(Theoph[Theoph$Subject==1, "Time"], Theoph[Theoph$Subject==1, "conc"])
DetSlope(Indometh[Indometh$Subject==2, "time"], Indometh[Indometh$Subject==2, "conc"])
```

gAUC

General Area Under the Curve

Description

General AUC function for Emax, TEmax and AUCs

Usage

```
gAUC(x, y, Ymax = "Emax", XofYmax = "TEmax", AUCname = "AUEClast", iAUC = "", 
Outer = "NEAREST")
```

Arguments

x	usually time
y	usually concentration or effect. This can be negative/
Ymax	usually Cmax or Emax
XofYmax	usually Tmax or TEmax
AUCname	usually AUClast or AUEClast
iAUC	a data.frame to calculate interval AUCs
Outer	indicates how to do the out of x range point

Details

This is a general purpose AUC function. It calculates only Cmax(Emax), Tmax(TEmax) and AUCs(AUECs). This can be used for effect(pharmacodynamic) data which has negative values. For concentration data, use IntAUC.

Value

Column names can vary according to the options.

Emax	maximum y value
TEmax	x value at the maximum y value
AUEClast	Area under the y versus x curve
iAUCs	Columns from iAUC input

Author(s)

Kyun-Seop Bae <k@acr.kr>

Examples

```
# For one subject
x = Theoph[Theoph$Subject=="1", "Time"]
y = Theoph[Theoph$Subject=="1", "conc"]
gAUC(x, y)

iAUC = data.frame(Name=c("AUC[0-12h]", "AUC[0-24h]"), Start=c(0,0), End=c(12,24))
gAUC(x, y, iAUC=iAUC)
```

gIntAUC*Calculate interval AUC of general form***Description**

It calculates interval AUC of general form. This is useful for pharmacodynamic data.

Usage

```
gIntAUC(x, y, t1, t2, Outer = "NEAREST")
```

Arguments

x	vector values of independent variable, usually time
y	vector values of dependent variable, usually concentration
t1	start time for AUC
t2	end time for AUC
Outer	indicates how to do the out of x range point

Details

This calculates an interval (partial) AUC (from t1 to t2) with the given series of x and y. If t1 and/or t2 cannot be found within x vector, it interpolates. If t1 and/or t2 are out of x range, it uses the nearest value. For concentration data, use IntAUC.

Value

return interval AUC value (scalar)

Author(s)

Kyun-Seop Bae <k@acr.kr>

See Also

[gAUC](#), [gInterpol](#), [tblAUC](#)

Examples

```
gIntAUC(Theoph[Theoph$Subject==1, "Time"], Theoph[Theoph$Subject==1, "conc"], t1=0.5, t2=11)
```

gInterpol*Interpolate y value for general y value not for concentration*

Description

It interpolates y value when a corresponding x value (xnew) does not exist within x vector

Usage

```
gInterpol(x, y, xnew, Outer="NEAREST")
```

Arguments

x	vector values of x-axis, usually time
y	vector values of y-axis, usually concentration
xnew	new x point to be interpolated, usually new time point
Outer	indicates how to do the out of x range point

Details

This function interpolate y value, if xnew is not in x vector. If xnew is in the x vector, it just returns the given x and y vector. This function usually is called by gIntAUC function Returned vector is sorted in the order of increasing x values.

Value

new x and y vector containing xnew and ynew point

Author(s)

Kyun-Seop Bae <k@acr.kr>

See Also

[gIntAUC](#)

Examples

```
x = 1:10 + 0.1
y = -2*x + 40.2
gInterpol(x, y, 1.5)
gInterpol(x, y, 0.5) # Out of range, Left
gInterpol(x, y, 11) # Out of range, Left
```

IntAUC	<i>Calculate interval AUC</i>
--------	-------------------------------

Description

It calculates interval AUC

Usage

```
IntAUC(x, y, t1, t2, Res, down = "Linear")
```

Arguments

x	vector values of independent variable, usually time
y	vector values of dependent variable, usually concentration
t1	start time for AUC
t2	end time for AUC
Res	result from sNCA function
down	either of "Linear" or "Log" to indicate the way to calculate AUC

Details

This calculates an interval (partial) AUC (from t1 to t2) with the given series of x and y. If t1 and/or t2 cannot be found within x vector, it interpolates according to the down option.

Value

return interval AUC value (scalar)

Author(s)

Kyun-Seop Bae <k@acr.kr>

References

1. Gabrielsson J, Weiner D. Pharmacokinetic and Pharmacodynamic Data Analysis - Concepts and Applications. 5th ed. 2016.
2. Shargel L, Yu A. Applied Biopharmaceutics and Pharmacokinetics. 7th ed. 2015.
3. Rowland M, Tozer TN. Clinical Pharmacokinetics and Pharmacodynamics - Concepts and Applications. 4th ed. 2011.
4. Gibaldi M, Perrier D. Pharmacokinetics. 2nd ed. revised and expanded. 1982.

See Also

[AUC](#), [Interpol](#)

Examples

```
Res = sNCA(Theoph[Theoph$Subject==1,"Time"], Theoph[Theoph$Subject==1, "conc"],
            dose=320, concUnit="mg/L")
IntAUC(Theoph[Theoph$Subject==1, "Time"], Theoph[Theoph$Subject==1, "conc"], t1=0.5, t2=11, Res)
```

Interpol

Interpolate y value

Description

It interpolates y value when a corresponding x value (xnew) does not exist within x vector

Usage

```
Interpol(x, y, xnew, Slope, b0, down = "Linear")
```

Arguments

x	vector values of x-axis, usually time
y	vector values of y-axis, usually concentration
xnew	new x point to be interpolated, usually new time point
Slope	slope of regression $\log(y) \sim x$
b0	y value of just left point of xnew
down	either of "Linear" or "Log" to indicate the way to interpolate

Details

This function interpolate y value, if xnew is not in x vector. If xnew is in x vector, it just returns the given x and y vector. This function usually is called by IntAUC function Returned vector is sorted in the order of increasing x values.

Value

new x and y vector containing xnew and ynew point

Author(s)

Kyun-Seop Bae <k@acr.kr>

See Also

[IntAUC](#)

Examples

```
x = 10:1 + 0.1
y = -2*x + 40.2
Interpol(x, y, 1.5)
Interpol(x, y, 1.5, down="Log")
```

LinAUC*Area Under the Curve(AUC) and Area Under the first Moment Curve(AUMC) by linear trapezoidal method***Description**

It calculates AUC and AUMC using the linear trapezoidal method

Usage

```
LinAUC(x, y)
```

Arguments

- | | |
|---|--|
| x | vector values of the independent variable, usually time |
| y | vector values of the dependent variable, usually concentration |

Details

This function returns AUC and AUMC by the linear trapezoidal method.

Value

- | | |
|------|-----------------------------------|
| AUC | area under the curve |
| AUMC | area under the first moment curve |

Author(s)

Kyun-Seop Bae <k@acr.kr>

References

1. Gabrielsson J, Weiner D. Pharmacokinetic and Pharmacodynamic Data Analysis - Concepts and Applications. 5th ed. 2016.
2. Shargel L, Yu A. Applied Biopharmaceutics and Pharmacokinetics. 7th ed. 2015.
3. Rowland M, Tozer TN. Clinical Pharmacokinetics and Pharmacodynamics - Concepts and Applications. 4th ed. 2011.
4. Gibaldi M, Perrier D. Pharmacokinetics. 2nd ed. revised and expanded. 1982.

See Also

[LogAUC](#), [AUC](#)

Examples

```
LinAUC(Theoph[Theoph$Subject==1, "Time"], Theoph[Theoph$Subject==1, "conc"])
AUC(Theoph[Theoph$Subject==1, "Time"], Theoph[Theoph$Subject==1, "conc"]) # compare the last line
```

LogAUC	<i>Area Under the Curve(AUC) and Area Under the first Moment Curve(AUMC) by linear-up log-down method</i>
--------	---

Description

It calculates AUC and AUMC using the linear-up log-down method

Usage

```
LogAUC(x, y)
```

Arguments

- | | |
|---|--|
| x | vector values of the independent variable, usually time |
| y | vector values of the dependent variable, usually concentration |

Details

This function returns AUC and AUMC by the linear-up log-down method.

Value

- | | |
|------|-----------------------------------|
| AUC | area under the curve |
| AUMC | area under the first moment curve |

Author(s)

Kyun-Seop Bae <k@acr.kr>

References

1. Gabrielsson J, Weiner D. Pharmacokinetic and Pharmacodynamic Data Analysis - Concepts and Applications. 5th ed. 2016.
2. Shargel L, Yu A. Applied Biopharmaceutics and Pharmacokinetics. 7th ed. 2015.
3. Rowland M, Tozer TN. Clinical Pharmacokinetics and Pharmacodynamics - Concepts and Applications. 4th ed. 2011.
4. Gibaldi M, Perrier D. Pharmacokinetics. 2nd ed. revised and expanded. 1982.

See Also

[LinAUC](#), [AUC](#)

Examples

```
LogAUC(Theoph[Theoph$Subject==1, "Time"], Theoph[Theoph$Subject==1, "conc"])
# Compare the last line with the above
AUC(Theoph[Theoph$Subject==1, "Time"], Theoph[Theoph$Subject==1, "conc"], down="Log")
```

Slope *Get the Slope of regression $\log(y) \sim x$*

Description

It calculates the slope with linear regression of $\log(y) \sim x$

Usage

`Slope(x, y)`

Arguments

x	vector values of the independent variable, usually time
y	vector values of the dependent variable, usually concentration

Details

With time-concentration curve, you frequently need to estimate slope in $\log(\text{concentration}) \sim \text{time}$. This function is usually called by `BestSlope` function, and you seldom need to call this function directly.

Value

R2	R-squared
R2ADJ	adjusted R-squared
LAMZNPT	number of points used for slope
LAMZ	negative of the slope, lambda_z
b0	intercept of the regression line
CORRXY	correlation of $\log(y)$ and x
LAMZLL	earliest x for lambda_z
LAMZUL	last x for lambda_z

Author(s)

Kyun-Seop Bae <k@acr.kr>

See Also

[BestSlope](#)

Examples

```
Slope(Indometh[Indometh$Subject==1, "time"], Indometh[Indometh$Subject==1, "conc"])
```

sNCA*Simplest NCA*

Description

This is the work-horse function for NCA.

Usage

```
sNCA(x, y, dose = 0, adm = "Extravascular", dur = 0, doseUnit = "mg", timeUnit = "h",
      concUnit = "ug/L", iAUC = "", down = "Linear", R2ADJ = 0.7, MW = 0, SS = FALSE,
      Keystring="", excludeDelta = 1)
```

Arguments

x	usually time
y	usually concentration
dose	given amount, not amount per body weight
adm	one of "Bolus" or "Infusion" or "Extravascular" to indicate drug administration mode
dur	duration of infusion
doseUnit	unit of dose
timeUnit	unit of time
concUnit	unit of concentration
iAUC	interval AUCs to calculate
down	either of "Linear" or "Log" to indicate the way to calculate AUC and AUMC
R2ADJ	Minimum adjusted R-square value to determine terminal slope automatically
MW	molecular weight of the drug
SS	if steady-state, this should be TRUE. AUCLST (AUClast) is used instead of AUCIFO (AUCinf) for the calculation of Vz (VZFO, VZO), CL (CLFO, CLO), and Vdss (VSSO).
Keystring	a text string to be shown at the plot in case of manual selection of terminal slope
excludeDelta	Improvement of R2ADJ larger than this value could exclude the last point. Default value 1 is for the compatibility with other software.

Details

This replaced previous IndiNCA. Author recommends to use excludeDelta option with about 0.3.

Value

CMAX	maximum concentration, Cmax
CMAXD	dose normalized Cmax, CMAX / Dose, Cmax / Dose
TMAX	time of maximum concentration, Tmax
TLAG	time to observe the first non-zero concentration, for extravascular administration only
CLST	last positive concentration observed, Clast
CLSTP	last positive concentration predicted, Clast_pred
TLST	time of last positive concentration, Tlast
LAMZHL	half-life by lambda z, $\ln(2)/\text{LAMZ}$
LAMZ	lambda_z negative of the best-fit terminal slope
LAMZLL	earliest time for LAMZ
LAMZUL	last time for LAMZ
LAMZNPT	number of points for LAMZ
CORRXY	correlation of log(concentration) and time
R2	R-squared
R2ADJ	R-squared adjusted
C0	back extrapolated concentration at time 0, for intravascular bolus administration only
AUCLST	AUC from 0 to TLST
AUCALL	AUC using all the given points, including trailing zero concentrations
AUCIFO	AUC infinity observed
AUCIFOD	AUCIFO / Dose
AUCIFP	AUC infinity predicted using CLSTP instead of CLST
AUCIFPD	AUCIFP / Dose
AUCPEO	AUC % extrapolation observed
AUCPEP	AUC % extrapolated for AUCIFP
AUCPBEO	AUC % back extrapolation observed, for bolus IV administration only
AUCPBEP	AUC % back extrapolation predicted with AUCIFP, for bolus IV administration only
AUMCLST	AUMC to the TLST
AUMCIFO	AUMC infinity observed using CLST
AUMCIFF	AUMC infinity determined by CLSTP
AUMCPEO	AUMC % extrapolated observed
AUMCPEP	AUMC % extrapolated predicted
MRTIVLST	mean residence time (MRT) to TLST, for intravascular administration
MRTIVIFO	mean residence time (MRT) infinity using CLST, for intravascular administration

MRTIVIFP	mean residence time (MRT) infinity using CLSTP, for intravascular administration
MRTEVLST	mean residence time (MRT) to TLST, for extravascular administration
MRTEVIFO	mean residence time (MRT) infinity using CLST, for extravascular administration
MRTEVIFFP	mean residence time (MRT) infinity using CLSTP, for extravascular administration
VZO	volume of distribution determined by LAMZ and AUCIFO, for intravascular administration
VZP	volume of distribution determined by LAMZ and AUCIFP, for intravascular administration
VZFO	VZO for extravascular administration, VZO/F, F is bioavailability
VZFP	VZP for extravascular administration, VZP/F, F is bioavailability
CLO	clearance using AUCIFO, for intravascular administration
CLP	clearance using AUCIFP, for intravascular administration
CLFO	CLO for extravascular administration, CLO/F, F is bioavailability
CLFP	CLP for extravascular administration, CLP/F, F is bioavailability
VSSO	volume of distribution at steady state using CLST, for intravascular administration only
VSSP	volume of distribution at steady state using CLSTP, for intravascular administration only

Author(s)

Kyun-Seop Bae <k@acr.kr>

References

Gabrielsson J, Weiner D. Pharmacokinetic and Pharmacodynamic Data Analysis - Concepts and Applications. 5th ed. 2016.

See Also

[help](#), [tblNCA](#)

Examples

```
# For one subject
x = Theoph[Theoph$Subject=="1","Time"]
y = Theoph[Theoph$Subject=="1","conc"]

sNCA(x, y, dose=320, doseUnit="mg", concUnit="mg/L", timeUnit="h")
sNCA(x, y, dose=320, concUnit="mg/L")

iAUC = data.frame(Name=c("AUC[0-12h]", "AUC[0-24h]"), Start=c(0,0), End=c(12,24))
sNCA(x, y, dose=320, doseUnit="mg", concUnit="mg/L", timeUnit="h", iAUC=iAUC)
```

```

MW = 180.164 # Molecular weight of theophylline

sNCA(x, y/MW, dose=320, doseUnit="mg", concUnit="mmol/L", timeUnit="h")
sNCA(x, y/MW, dose=320, doseUnit="mg", concUnit="mmol/L", timeUnit="h", MW=MW)
sNCA(x, y, dose=320/MW, doseUnit="mmol", concUnit="mg/L", timeUnit="h", MW=MW)
sNCA(x, y/MW, dose=320/MW, doseUnit="mmol", concUnit="mmol/L", timeUnit="h", MW=MW)

sNCA(x, y/MW, dose=320/MW, doseUnit="mmol", concUnit="mmol/L", timeUnit="h", MW=MW)
sNCA(x, y/MW, doseUnit="mmol", concUnit="mmol/L", timeUnit="h", MW=MW)
sNCA(x, y/MW, dose=as.numeric(NA), doseUnit="mmol", concUnit="mmol/L", timeUnit="h",
      MW=MW)

sNCA(x, y, dose=320, concUnit="mg/L", timeUnit="hr")
sNCA(x*60, y, dose=320, concUnit="mg/L", timeUnit="min")

```

tblAUC*Table output of gAUCs***Description**

Do multiple AUCs and returns a result table. See gNCA for more detail i.e. iAUC

Usage

```
tblAUC(Data, key = "Subject", colX = "Time", colY = "Y", iAUC = "",  
       Ymax = "Emax", XofYmax = "TEmax", AUCname = "AUEClast", Outer = "NEAREST")
```

Arguments

Data	data table name
key	column names of Data to be shown in the output table
colX	column name for x axis
colY	column name for y axis
iAUC	a data.frame to calculate interval AUCs
Ymax	usually Cmax or Emax
XofYmax	usually Tmax or TEmax
AUCname	usually AUClast or AUEClast
Outer	indicates how to do the out of x range point

Details

Tabular output of AUC with many subjects. This calculates only Cmax(Emax), Tmax(TEmax), AUCs

Value

Basically same with [gAUC](#)

Author(s)

Kyun-Seop Bae <k@acr.kr>

See Also

[help](#), [gAUC](#)

Examples

```
tblAUC(Theoph, key="Subject", colX="Time", colY="conc")
iAUC = data.frame(Name=c("AUC[0-12h]", "AUC[0-24h]"), Start=c(0,0), End=c(12,24))
tblAUC(Indometh, key="Subject", colX="time", colY="conc", iAUC=iAUC)
```

tblNCA

Table output NCA

Description

Do multiple NCA and returns a result table. See [sNCA](#) for more detail i.e. iAUC

Usage

```
tblNCA(concData, key = "Subject", colTime = "Time", colConc = "conc", dose = 0,
       adm = "Extravascular", dur = 0, doseUnit = "mg", timeUnit = "h",
       concUnit = "ug/L", down = "Linear", R2ADJ = 0, MW = 0, SS = FALSE,
       iAUC = "", excludeDelta = 1)
```

Arguments

concData	concentration data table
key	column names of concData to be shown in the output table
colTime	column name for time
colConc	column name for concentration
dose	administered dose
adm	one of "Bolus" or "Infusion" or "Extravascular" to indicate drug administration mode
dur	duration of infusion
doseUnit	unit of dose
timeUnit	unit of time
concUnit	unit of concentration

down	method to calculate AUC, "Linear" or "Log"
R2ADJ	Lowest threshold of adjusted R-square value to do manual slope determination
MW	molecular weight of drug
SS	if steady-state, this should be TRUE. AUCLST (AUClast) is used instead of AUCIFO (AUCinf) for the calculation of Vz (VZFO, VZO), CL (CLFO, CLO), and Vdss (VSSO).
iAUC	data.frame for interval AUC
excludeDelta	Improvement of R2ADJ larger than this value could exclude the last point. Default value 1 is for the compatibility with other software.

Details

Tabular output of NCA with many subjects. Author recommends to use excludeDelta option with about 0.3.

Value

Basically same with [sNCA](#)

Author(s)

Kyun-Seop Bae <k@acr.kr>

See Also

[help](#), [sNCA](#)

Examples

```
tblNCA(Theoph, key="Subject", dose=320, concUnit="mg/L")
tblNCA(Indometh, key="Subject", colTime="time", colConc="conc", dose=25,
       adm="Infusion", dur=0.5, concUnit="mg/L")
```

Description

It displays CDISC PP output units and multiplication factor for them.

Usage

```
Unit(code = "", timeUnit = "h", concUnit = "ng/mL", doseUnit = "mg", MW = 0)
```

Arguments

code	vector of PPTESTCD
timeUnit	unit of time
concUnit	unit of concentration
doseUnit	unit of dose
MW	molecular weight of drug

Value

row names	PPTESTCD
Unit	unit
Factor	internal multiplication factor

Author(s)

Kyun-Seop Bae <k@acr.kr>

Examples

```
Unit(concUnit="ug/L", doseUnit="mg")
Unit(concUnit="ng/L", doseUnit="mg")

Unit(concUnit="umol/L", doseUnit="mmol")
Unit(concUnit="nmol/L", doseUnit="mmol")

Unit(concUnit="mmol/L", doseUnit="mg", MW=500)
Unit(concUnit="umol/L", doseUnit="mg", MW=500)
Unit(concUnit="nmol/L", doseUnit="mg", MW=500)
Unit(concUnit="nmol/mL", doseUnit="mg", MW=500)

Unit(concUnit="ug/L", doseUnit="mmol", MW=500)
Unit(concUnit="ug/L", doseUnit="mol", MW=500)
Unit(concUnit="ng/L", doseUnit="mmol", MW=500)
Unit(concUnit="ng/mL", doseUnit="mmol", MW=500)

Unit(concUnit="nmol/L", doseUnit="mg")
Unit(concUnit="ug/L", doseUnit="mmol")
```

UnitUrine

Returns a conversion factor for the amount calculation from urine concentration and volume

Description

You can get a conversion factor for the multiplication: conc * vol * factor = amount in the given unit.

Usage

```
UnitUrine(conU = "ng/mL", volU = "mL", amtU = "mg", MW = 0)
```

Arguments

conU	concentration unit
volU	volume unit
amtU	amount unit
MW	molecular weight

Value

Factor	conversion factor for multiplication with the unit in name
--------	--

Author(s)

Kyun-Seop Bae <k@acr.kr>

Examples

```
UnitUrine()
UnitUrine("ng/mL", "mL", "mg")
UnitUrine("ug/L", "mL", "mg")
UnitUrine("ug/L", "L", "mg")

UnitUrine("ng/mL", "mL", "g")

UnitUrine("ng/mL", "mL", "mol", MW=500)
UnitUrine("ng/mL", "mL", "mmol", MW=500)
UnitUrine("ng/mL", "mL", "umol", MW=500)
```

Index

- * **AUC**
 - AUC, 3
 - gIntAUC, 8
 - IntAUC, 10
 - LinAUC, 12
 - LogAUC, 13
 - * **Output Form**
 - sNCA, 15
 - tblNCA, 19
 - * **interpolation**
 - gInterpol, 9
 - Interpol, 11
 - * **interval AUC**
 - gIntAUC, 8
 - gInterpol, 9
 - IntAUC, 10
 - Interpol, 11
 - * **partial AUC**
 - gIntAUC, 8
 - gInterpol, 9
 - IntAUC, 10
 - Interpol, 11
 - * **slope**
 - BestSlope, 4
 - DetSlope, 5
 - Slope, 14
- AUC, 3, 10, 12, 13
- BestSlope, 4, 14
- DetSlope, 5
- gAUC, 6, 8, 19
- gIntAUC, 8, 9
- gInterpol, 8, 9
- help, 17, 19, 20
- IntAUC, 10, 11
- Interpol, 10, 11
- LinAUC, 4, 12, 13
- LogAUC, 4, 12, 13
- NonCompart (NonCompart-package), 2
- NonCompart-package, 2
- Slope, 5, 6, 14
- sNCA, 15, 20
- tblAUC, 8, 18
- tblNCA, 17, 19
- Unit, 20
- UnitUrine, 21