

Package ‘PLEXI’

August 9, 2023

Type Package

Title Multiplex Network Analysis

Version 1.0.0

Description

Interactions between different biological entities are crucial for the function of biological systems. In such networks, nodes represent biological elements, such as genes, proteins and mi-crobes, and their interactions can be defined by edges, which can be either binary or weighted. The dysregulation of these networks can be associated with different clinical condi-tions such as diseases and response to treatments.

However, such variations often occur locally and do not concern the whole network.

To capture local variations of such networks, we propose multiplex network differential analy-sis (MNDA).

MNDA allows to quantify the variations in the local neighborhood of each node (e.g. gene) be-tween the two given clinical states, and to test for statistical significance of such variation.

Yousefi et al. (2023) <[doi:10.1101/2023.01.22.525058](https://doi.org/10.1101/2023.01.22.525058)>.

License GPL (>= 3)

Encoding UTF-8

RoxygenNote 7.2.3

Imports assertthat, igraph, keras, ggraph, ggplot2, aggregation,
stats, graphics

NeedsCompilation no

Author Behnam Yousefi [aut, cre, cph],
Farzaneh Firoozbakht [aut]

Maintainer Behnam Yousefi <yousefi.bme@gmail.com>

Repository CRAN

Date/Publication 2023-08-09 15:50:03 UTC

R topics documented:

as_igraph	2
as_plexi_graph	3
distance	3

ednn	4
ednn_io_prepare	5
example_data	6
network_gen	7
plexi_distance_test1_isn	7
plexi_distance_test_isn	8
plexi_embedding	9
plexi_embedding_2layer	11
plexi_node_detection_2layer	12
plexi_node_distance	13
p_val_count	14
p_val_norm	14
p_val_rank	15
Rank	16
rep_random_walk	17
subgraph_difference_plot	18
subgraph_plot	19
weightd_random_walk	20
Index	21

as_igraph	<i>Convert plexi graph data to igraph</i>
-----------	---

Description

Convert plexi graph data to igraph

Usage

```
as_igraph(plexi.graph, edge.threshold = 0)
```

Arguments

plexi.graph plexi graph data
edge.threshold numeric

Value

igraph object

Examples

```
data = example_data()
graph = as_igraph(plexi.graph = data[["plexi_graph_example"]])
```

as_plexi_graph	<i>Convert adjacency matrix to plexi graph data</i>
----------------	---

Description

Convert adjacency matrix to plexi graph data

Usage

```
as_plexi_graph(adj.list, outcome = NULL)
```

Arguments

adj.list	list of adjacency matrices with matching nodes
outcome	graph outcomes or graph labels. If NULL, outcome = 1:N_graphs.

Value

plexi.graph data

Examples

```
data = example_data()
adj.list = list(data[["adj_mat_example"]], data[["adj_mat_example"]])
graph.data = as_plexi_graph(adj.list)
```

distance	<i>Function to calculate distance between two vectors</i>
----------	---

Description

Function to calculate distance between two vectors

Usage

```
distance(x, y, method = "cosine")
```

Arguments

x	numeric vector
y	numeric vector
method	distance calculation method: cosine (default), dot.prod, euclidian, manhattan, chebyshev, coassociation

Value

the distance value

Examples

```
x = c(1,2,3)
y = c(6,4,6)
distance(x,y)
```

 ednn

Encoder decoder neural network (EDNN) function

Description

Encoder decoder neural network (EDNN) function

Usage

```
ednn(
  x,
  y,
  x.test,
  embedding.size = 2,
  epochs = 10,
  batch.size = 5,
  l2reg = 0,
  demo = TRUE,
  verbose = FALSE
)
```

Arguments

x	concatenated adjacency matrices for different layers containing the nodes in training phase
y	concatenated random walk probability matrices for different layers containing the nodes in training phase
x.test	concatenated adjacency matrices for different layers containing the nodes in test phase. Can be = X for transductive inference.
embedding.size	the dimension of embedding space, equal to the number of the bottleneck hidden nodes.
epochs	maximum number of pocks. An early stopping callback with a patience of 5 has been set inside the function (default = 10).
batch.size	batch size for learning (default = 5).
l2reg	the coefficient of L2 regularization for the input layer (default = 0).
demo	a boolean vector to indicate this is a demo example or not
verbose	if <i>TRUE</i> a progress bar is shown.

Value

The embedding space for x.test.

Examples

```
myNet = network_gen(n.nodes = 50)
graphData = myNet[["data_graph"]]
edge.list = graphData[,1:2]
edge.weight = graphData[,3:4]
XY = ednn_io_prepare(edge.list, edge.weight)
X = XY[["X"]]
Y = XY[["Y"]]
embeddingSpace = ednn(x = X, y = Y, x.test = X)
```

ednn_io_prepare

Preparing the input and output of the EDNN for a multiplex graph

Description

Preparing the input and output of the EDNN for a multiplex graph

Usage

```
ednn_io_prepare(
  edge.list,
  edge.weight,
  outcome = NULL,
  indiv.index = NULL,
  edge.threshold = 0,
  walk.rep = 10,
  n.steps = 5,
  random.walk = TRUE,
  verbose = TRUE
)
```

Arguments

edge.list	edge list as a dataframe with two columns.
edge.weight	edge weights as a dataframe. Each column corresponds to a graph. By default, the colnames are considered as outcomes unless indicated in outcome argument.
outcome	clinical outcomes for each graph. If not mentioned, the colnames(edge.weight) are considered by default.
indv.index	the index of individual networks.
edge.threshold	numeric value to set edge weights below the threshold to zero (default: 0). the greater edge weights do not change.

walk.rep	number of repeats for the random walk (default: 100).
n.steps	number of the random walk steps (default: 5).
random.walk	boolean value to enable the random walk algorithm (default: TRUE).
verbose	if <i>TRUE</i> a progress bar is shown.

Value

the input and output required to train the EDNN

Examples

```
myNet = network_gen(n.nodes = 50)
graphData = myNet[["data_graph"]]
edge.list = graphData[,1:2]
edge.weight = graphData[,3:4]
XY = ednn_io_prepare(edge.list, edge.weight)
X = XY[["X"]]
Y = XY[["Y"]]
```

example_data

Example Data

Description

Example Data

Usage

```
example_data()
```

Value

example data as a list: "adj_mat_example", "igraph_example", "plexi_graph_example"

Examples

```
data = example_data()
```

network_gen	<i>Multiplex Network Generation</i>
-------------	-------------------------------------

Description

Multiplex Network Generation

Usage

```
network_gen(n.nodes = 100, n.var.nodes = 5, n.var.nei = 90, noise.sd = 0.1)
```

Arguments

n.nodes	number of nodes in the graph
n.var.nodes	number of nodes whose neighborhood should change from layer 1 to 2
n.var.nei	number of neighbors that should be changing from layer 1 to 2
noise.sd	the standard deviation of the noise added to the edge weights

Details

In this script we generate random pairs of gene co-expression networks, which are different only in a few (pre-set) number of nodes.

Value

No return value, called to plot subgraphs

Examples

```
myNet = network_gen(n.nodes = 100)
graphData = myNet[["data_graph"]]
varNodes = myNet[["var_node_set"]]
```

plexi_distance_test1_isn	<i>Test the extremeness of embedding distances of local neighbors.</i>
--------------------------	--

Description

Test the extremeness of embedding distances of local neighbors.

Usage

```
plexi_distance_test1_isn(distance, p.adjust.method = "none")
```

Arguments

`distance` a distance list obtained by the `plexi_node_distance()` function.

`p.adjust.method` method for adjusting p-value (including methods on `p.adjust.methods`). If set to "none" (default), no adjustment will be performed.

Details

The adjusted p-values for each node is calculated based on their distance.

Value

The adjusted pvalues for each node.

Examples

```
ISN1 = network_gen(n.nodes = 50, n.var.nodes = 5, n.var.nei = 40, noise.sd = .01)
ISN2 = network_gen(n.nodes = 50, n.var.nodes = 5, n.var.nei = 40, noise.sd = .01)
graph_data = cbind(ISN1[["data_graph"]], ISN2[["data_graph"]][,3:4])
embeddingSpaceList = plexi_embedding(graph.data=graph_data, outcome=c(1,2,1,2),
  indiv.index=c(1,1,2,2), train.rep=2, random.walk=FALSE)
Dist = plexi_node_distance(embeddingSpaceList)
Result = plexi_distance_test1_isn(Dist)
```

`plexi_distance_test_isn`

Test the embedding distances of local neighbors change between the two conditions for ISNs.

Description

Test the embedding distances of local neighbors change between the two conditions for ISNs.

Usage

```
plexi_distance_test_isn(
  distance,
  y,
  stat.test = "wilcox.test",
  p.adjust.method = "none"
)
```


Arguments

distance	a distance list obtained by the <code>plexi_node_distance()</code> function.
y	vector with the length equal to the number of individuals.
stat.test	statistical test used to detect the nodes <code>c("t.test", "wilcox.test")</code> (default: <code>wilcox.test</code>)
p.adjust.method	method for adjusting p-value (including methods on <code>p.adjust.methods</code>). If set to "none" (default), no adjustment will be performed.

Details

The adjusted p-values for each node is calculated based on their distance variation between the two conditions.

Value

The adjusted pvalues for each node.

Examples

```
ISN1 = network_gen(n.nodes = 50, n.var.nodes = 5, n.var.nei = 40, noise.sd = .01)
ISN2 = network_gen(n.nodes = 50, n.var.nodes = 5, n.var.nei = 40, noise.sd = .01)
graph_data = cbind(ISN1[["data_graph"]], ISN1[["data_graph"]][,3:4])
embeddingSpaceList = plexi_embedding(graph.data=graph_data, outcome=c(1,2,1,2),
indv.index=c(1,1,2,2), train.rep=2, random.walk=FALSE)
Dist = plexi_node_distance(embeddingSpaceList)
Result = plexi_distance_test_isn(Dist, y = c(1,2))
```

plexi_embedding

Calculate the embedding space for a multiplex network

Description

Calculate the embedding space for a multiplex network

Usage

```
plexi_embedding(
  graph.data,
  outcome,
  indv.index = NULL,
  edge.threshold = 0,
  train.rep = 50,
  embedding.size = 2,
  epochs = 10,
  batch.size = 5,
```

```

    l2reg = 0,
    walk.rep = 100,
    n.steps = 5,
    random.walk = TRUE,
    demo = TRUE,
    verbose = FALSE
  )

```

Arguments

graph.data	dataframe of the graph data containing edge list and edge weights. column 1 and 2 consisting of the edge list (undirected). column 3 and 4 consisting the edge weights corresponding to each graph, respectively.
outcome	a vector of outcomes for each network.
indv.index	the index of individual networks.
edge.threshold	numeric value to set edge weights below the threshold to zero (default: 0). the greater edge weights do not change.
train.rep	numeric value to set the number of EDNN training repeats (default: 50).
embedding.size	the dimension of embedding space, equal to the number of the bottleneck hidden nodes (default: 5).
epochs	maximum number of pocks. An early stopping callback with a patience of 5 has been set inside the function (default = 10).
batch.size	batch size for learning (default = 5).
l2reg	the coefficient of L2 regularization for the input layer (default = 0).
walk.rep	number of repeats for the random walk (default: 100).
n.steps	number of the random walk steps (default: 5).
random.walk	boolean value to enable the random walk algorithm (default: TRUE).
demo	a boolean vector to indicate this is a demo example or not
verbose	if <i>TRUE</i> a progress bar is shown.

Value

a list of embedding spaces for each node.

Examples

```

myNet = network_gen(n.nodes = 50, n.var.nodes = 5, n.var.nei = 40, noise.sd = .01)
graph_data = myNet[["data_graph"]]
embeddingSpaceList = plexi_embedding(graph.data=graph_data, outcome=c(1,2),
train.rep=2, random.walk=FALSE)

```

plexi_embedding_2layer

Calculate the embedding space for a two layer multiplex network

Description

Calculate the embedding space for a two layer multiplex network

Usage

```
plexi_embedding_2layer(
  graph.data,
  edge.threshold = 0,
  train.rep = 50,
  embedding.size = 2,
  epochs = 10,
  batch.size = 5,
  l2reg = 0,
  walk.rep = 100,
  n.steps = 5,
  random.walk = TRUE,
  null.perm = TRUE,
  demo = TRUE,
  verbose = FALSE
)
```

Arguments

graph.data	dataframe of the graph data containing edge list and edge weights. column 1 and 2 consisting of the edge list (undirected). column 3 and 4 consisting the edge weights corresponding to each graph, respectively.
edge.threshold	numeric value to set edge weights below the threshold to zero (default: 0). the greater edge weights do not change.
train.rep	numeric value to set the number of EDNN training repeats (default: 50).
embedding.size	the dimension of embedding space, equal to the number of the bottleneck hidden nodes (default: 5).
epochs	maximum number of pocks. An early stopping callback with a patience of 5 has been set inside the function (default = 10).
batch.size	batch size for learning (default = 5).
l2reg	the coefficient of L2 regularization for the input layer (default = 0).
walk.rep	number of repeats for the random walk (default: 100).
n.steps	number of the random walk steps (default: 5).
random.walk	boolean value to enable the random walk algorithm (default: TRUE).

null.perm	boolean to enable permuting two random graphs and embed them, along with the main two graphs, for the null distribution (default: TRUE).
demo	a boolean vector to indicate this is a demo example or not
verbose	if <i>TRUE</i> a progress bar is shown.

Value

a list of embedding spaces for each node.

Examples

```
myNet = network_gen(n.nodes = 50, n.var.nodes = 5, n.var.nei = 40, noise.sd = .01)
graph_data = myNet[["data_graph"]]
embeddingSpaceList = plexi_embedding_2layer(graph.data=graph_data, train.rep=5, walk.rep=5)
```

plexi_node_detection_2layer

Detecting the nodes whose local neighbors change between the two conditions.

Description

Detecting the nodes whose local neighbors change between the two conditions.

Usage

```
plexi_node_detection_2layer(
  embeddingSpaceList,
  p.adjust.method = "none",
  alpha = 0.05,
  rank.prc = 0.1,
  volcano.plot = TRUE,
  ranksum.sort.plot = FALSE
)
```

Arguments

embeddingSpaceList	a list obtained by the plexi_embedding_2layer() function.
p.adjust.method	method for adjusting p-value (including methods on p.adjust.methods). If set to "none" (default), no adjustment will be performed.
alpha	numeric value of significance level (default: 0.05)
rank.prc	numeric value of the rank percentage threshold (default: 0.1)
volcano.plot	boolean value for generating the Volcano plot (default: TRUE)
ranksum.sort.plot	boolean value for generating the sorted rank sum plot (default: FALSE)

Details

Calculating the distance of node pairs in the embedding space and check their significance. To find the significantly varying nodes in the 2-layer-network, the distance between the corresponding nodes are calculated along with the null distribution. The null distribution is obtained based on the pairwise distances on null graphs. if in `plexi_embedding_2layer` function `null.perm=FALSE`, the multiplex network does not have the two randomly permuted graphs, thus the distances between all the nodes will be used for the null distribution.

Value

the highly variable nodes

Examples

```
myNet = network_gen(n.nodes = 50, n.var.nodes = 5, n.var.nei = 40, noise.sd = .01)
graph_data = myNet[["data_graph"]]
embeddingSpaceList = plexi_embedding_2layer(graph.data=graph_data, train.rep=5, walk.rep=5)
Nodes = plexi_node_detection_2layer(embeddingSpaceList)
```

`plexi_node_distance` *Detecting the nodes whose local neighbors change between the two conditions for ISNs.*

Description

Detecting the nodes whose local neighbors change between the two conditions for ISNs.

Usage

```
plexi_node_distance(embedding.space.list)
```

Arguments

`embedding.space.list`
a list obtained by the `plexi_embedding_2layer()` function.

Details

Calculating the distance of node pairs in the embedding space and check their significance. To find the significantly varying nodes in the 2-layer-network, the distance between the corresponding nodes are calculated along with the null distribution. The null distribution is obtained based on the pairwise distances on null graphs. if in `plexi_embedding_2layer` function `null.perm=FALSE`, the multiplex network does not have the two randomly permuted graphs, thus the distances between all the nodes will be used for the null distribution.

Value

the distances for each repeat

Examples

```
myNet = network_gen(n.nodes = 50, n.var.nodes = 5, n.var.nei = 40, noise.sd = .01)
graph_data = myNet[["data_graph"]]
embeddingSpaceList = plexi_embedding(graph.data=graph_data, outcome=c(1,2),
indv.index=c(1,1), train.rep=2, random.walk=FALSE)
Dist = plexi_node_distance(embeddingSpaceList)
```

p_val_count

Calculate p.value for x given set of null values using counts

Description

Calculate p.value for x given set of null values using counts

Usage

```
p_val_count(x, null.values, alternative = "two.sided")
```

Arguments

x numeric value
null.values a numeric vector of null distribution samples
alternative alterative test including: "two.sided" [default], "greater", and "less"

Value

p.value

Examples

```
p.val = p_val_count(1, 1:100)
```

p_val_norm

Calculate p.value for x given set of null values using a Gaussian null pdf

Description

Calculate p.value for x given set of null values using a Gaussian null pdf

Usage

```
p_val_norm(x, null.values, alternative = "two.sided")
```

Arguments

x numeric value
null.values a numeric vector of null distribution samples
alternative alterative test including: "two.sided" [default], "greater", and "less"

Value

p.value

Examples

```
p.val = p_val_norm(1, rnorm(1000,0,1))
```

p_val_rank *Calculate p.value for x given a set of null values using ranks*

Description

Calculate p.value for x given a set of null values using ranks

Usage

```
p_val_rank(x, null.values, alternative = "two.sided")
```

Arguments

x numeric value
null.values a numeric vector of null distribution samples
alternative alterative test including: "two.sided" [default], "greater", and "less"

Value

p.value

Examples

```
p.val = p_val_rank(1, 1:100)
```

Rank	<i>Ranking a vector</i>
------	-------------------------

Description

Ranking a vector

Usage

```
Rank(x, decreasing = FALSE)
```

Arguments

x	a numeric vector
decreasing	logical. Should the sort order be increasing or decreasing? (default: FALSE)

Details

hint: What is the difference between Order and Rank

Order: [the index of the greatest number, ..., the index of the smallest number]

Rank: [the rank of the 1st number, ..., the rank of the last number]

In Rank, the order of the numbers remains constant so can be used for ranksum.

ex)

```
> a = c(10, 20, 50, 30, 40)
```

```
> order(a)
```

```
[1] 1 2 4 5 3]]
```

```
> Rank(a)
```

```
[1] 1 2 5 3 4
```

Value

the rank of the vector elements

Examples

```
a = c(10, 20, 50, 30, 40)
```

```
Rank(a)
```

rep_random_walk	<i>Repetitive Fixed-length (weighted) random walk algorithm</i>
-----------------	---

Description

Repetitive Fixed-length (weighted) random walk algorithm

Usage

```
rep_random_walk(  
  graph,  
  Nrep = 100,  
  Nstep = 5,  
  weighted_walk = TRUE,  
  verbose = TRUE  
)
```

Arguments

graph	an igraph object
Nrep	number of repeats (default:100)
Nstep	maximum number steps (default:5)
weighted_walk	choose the <i>weighted walk</i> algorithm if <i>TRUE</i> and <i>simple random walk</i> if <i>FALSE</i> . (default: <i>TRUE</i>)
verbose	if <i>TRUE</i> a progress bar is shown.

Value

Steps (S): The total number of times a node is visited starting from the corresponding node in the row. Probabilities (P): The node visit probabilities starting from the corresponding node in the row.

Examples

```
data = example_data()  
RW = rep_random_walk(graph = data[["igraph_example"]])  
Steps = RW[["Steps"]]  
Probabilities = RW[["Probabilities"]]
```

subgraph_difference_plot

Visualization of a difference subgroup using a circular graph

Description

Visualization of a difference subgroup using a circular graph

Usage

```
subgraph_difference_plot(
  plexi.graph,
  node.importance,
  n.var.nodes = 5,
  n.neigh = 10,
  diff.threshold = 0,
  edge.width = c(0.5, 4)
)
```

Arguments

plexi.graph	plexi.graph data
node.importance	named numeric vector of the node importance to sort the nodes clockwise.
n.var.nodes	number of variable nodes to show
n.neigh	number of neighboring nodes to show
diff.threshold	edge threshold
edge.width	numeric value to adjust the thickness of the edges in plot. Two modes are defined: [i] two numbers indicating the min and max (default: c(0.5,4)); or [ii] a single number that weights the min/max of original edge weights.

Value

nothing to return

Examples

```
myNet = network_gen(n.nodes = 100, n.var.nodes = 5, n.var.nei = 90, noise.sd = .01)
graph_data = myNet[["data_graph"]]
node_importance_dummy = 1:100
names(node_importance_dummy) = 1:100
subgraph_difference_plot(graph_data, node.importance = node_importance_dummy)
```

`subgraph_plot`*Visualization of a subgroup using a circular graph*

Description

Visualization of a subgroup using a circular graph

Usage

```
subgraph_plot(  
  graph,  
  node_set,  
  labels = NULL,  
  node.importance = NULL,  
  n.nodes = NULL,  
  node_size = 5,  
  font_size = 4,  
  edge_width = c(0.5, 4),  
  margin = 2.5  
)
```

Arguments

<code>graph</code>	an igraph object
<code>node_set</code>	the names or indices of the nodes around which the subgroup is plotted.
<code>labels</code>	the labels of the nodes to be indicated. Labels should be a named vector if the <code>node_set</code> consists of the node names.
<code>node.importance</code>	named numeric vector of the node importance to sort the nodes clockwise.
<code>n.nodes</code>	number of nodes to be displayed. If <code>NULL</code> , all the <code>node_set</code> and their neighbors are considered.
<code>node_size</code>	size of the nodes in plot (default: 5)
<code>font_size</code>	font size of labels if available (default: 4)
<code>edge_width</code>	numeric value to adjust the thickness of the edges in plot. Two modes are defined: [i] two numbers indicating the min and max (default: <code>c(0.5,4)</code>); or [ii] a single number that weights the min/max of original edge weights.
<code>margin</code>	the figure margin (default: 2.5)

Details

This function plots a sub-graph given by a set of nodes as circular plot. the main inputs to the function are: a graph (as an igraph object) and a set of nodes (e.g. highly variable nodes) around which the subgroup is calculated.

Value

nothing to return

Examples

```
data = example_data()
subgraph_plot(graph = data[["igraph_example"]], node_set = "a")
```

weightd_random_walk *Weighted Random Walk algorithm*

Description

Weighted Random Walk algorithm

Usage

```
weightd_random_walk(graph, startNode, maxStep = 5, node_names = FALSE)
```

Arguments

graph	an igraph object
startNode	the starting node (i.e. a node name or a node index)
maxStep	maximum number steps (default:5)
node_names	a list of names for nodes

Value

The set of nodes passed by the random walker.

Examples

```
data = example_data()
nodePath = weightd_random_walk(graph = data[["igraph_example"]], startNode = 1)
```

Index

as_igraph, [2](#)
as_plexi_graph, [3](#)

distance, [3](#)

ednn, [4](#)
ednn_io_prepare, [5](#)
example_data, [6](#)

network_gen, [7](#)

p_val_count, [14](#)
p_val_norm, [14](#)
p_val_rank, [15](#)
plexi_distance_test1_isn, [7](#)
plexi_distance_test_isn, [8](#)
plexi_embedding, [9](#)
plexi_embedding_2layer, [11](#)
plexi_node_detection_2layer, [12](#)
plexi_node_distance, [13](#)

Rank, [16](#)
rep_random_walk, [17](#)

subgraph_difference_plot, [18](#)
subgraph_plot, [19](#)

weightd_random_walk, [20](#)