

Package ‘inedemogR’

October 5, 2026

Title Tidy Access to Spanish INE Demographic Data

Version 0.2.0

Description Provides tidy, harmonized access to demographic data from the Spanish National Statistics Institute (INE) fenomenos demograficos domain, including population, births, and deaths, retrieved live via the official 'ineapir' API wrapper, with optional spatial integration at municipality and province level via 'mapSpain'. Mortality indicators follow the Human Mortality Database Methods Protocol, including the average age at death in infancy method of Andreev and Kingkade (2015) <[doi:10.4054/DemRes.2015.33.13](https://doi.org/10.4054/DemRes.2015.33.13)>.

License MIT + file LICENSE

Encoding UTF-8

RoxygenNote 7.3.3

Imports dplyr, ggplot2, httr2, ineapir, mapSpain, purrr, readr, rlang, scales, sf, stringi, stringr, tibble, tidyr

Suggests mockery, R.rsp, testthat (>= 3.0.0), withr

Config/testthat/edition 3

Depends R (>= 4.1.0)

LazyData true

Collate 'helpers.R' 'death_rates.R' 'life_tables.R'
'abridged_life_tables.R' 'births.R' 'data.R' 'deaths.R'
'decomposition.R' 'download_ine_data.R' 'exposure.R'
'get_ine_demog.R' 'get_ine_geo.R' 'hmd_write.R' 'indicators.R'
'inedemogR-package.R' 'lexis.R' 'list_ine_indicators.R'
'plot_demog.R' 'plot_ine_map.R' 'population.R'
'update_ine_data.R'

VignetteBuilder R.rsp

NeedsCompilation no

Author J. R. Caro-Barrera [aut, cre, cph]

Maintainer J. R. Caro-Barrera <jrcaro@uco.es>

Repository CRAN

Date/Publication 2026-10-05 13:30:02 UTC

Contents

age_dependency_ratio	3
age_specific_fertility_rate	4
aging_index	5
andreev_kingkade_a0	6
birth_death_ratio	7
build_abridged_life_table	7
build_abridged_life_tables	8
build_life_table	9
build_life_tables	10
compute_death_rates	11
compute_exposure	13
crude_birth_rate	14
crude_death_rate	15
decompose_life_expectancy	15
download_ine_data	17
general_fertility_rate	18
get_ine_births	19
get_ine_births_by_age	20
get_ine_deaths	21
get_ine_demog	23
get_ine_geo	24
get_ine_population	25
gross_reproduction_rate	26
ine_variables	27
infant_mortality_rate	28
life_expectancy	29
life_expectancy_summary	30
list_ine_indicators	30
map_indicator	31
map_life_expectancy	32
mean_age_at_childbearing	33
net_reproduction_rate	34
plot_demog_trend	35
plot_ine_map	35
plot_lexis_diagram	37
plot_population_pyramid	38
rate_of_natural_increase	39
sex_ratio	40
total_fertility_rate	41
update_ine_data	41
validate_abridged_life_table	42
validate_births	43
validate_births_by_age	44
validate_deaths	44
validate_deaths_age	45
validate_death_rates	46

<i>age_dependency_ratio</i>	3
validate_exposure	47
validate_life_table	47
validate_population	48
Index	49

<i>age_dependency_ratio</i>	<i>Age dependency ratios</i>
-----------------------------	------------------------------

Description

Computes youth, old-age, and total age dependency ratios per province and year from age-disaggregated population data. Requires an age breakdown, so it operates on `get_ine_population()`'s output, not `get_ine_demog()`'s `population_total` indicator (which has no age column and cannot be used here).

Usage

```
age_dependency_ratio(pop_df, young_max = 14L, old_min = 65L)
```

Arguments

- `pop_df` Population tibble as returned by `get_ine_population()`\$data (columns `nuts3_code`, `province_name`, `year`, `age`, `total`).
- `young_max` Integer, the maximum age counted as "young" (default 14, i.e. ages 0-14).
- `old_min` Integer, the minimum age counted as "old" (default 65).

Value

A tibble with `nuts3_code`, `province_name`, `year`, `youth_dependency_ratio`, `old_age_dependency_ratio`, `total_dependency_ratio` (all per 100 working-age population).

Examples

```
pop <- tibble::tibble(
  nuts3_code = "ES111", province_name = "A Coruna", year = 2023,
  age = c(0, 20, 70), total = c(100, 300, 150)
)
age_dependency_ratio(pop)
```

age_specific_fertility_rate
Age-specific fertility rates (ASFR)

Description

Computes age-specific fertility rates per province, year, and single year of mother's age, following INE's methodology for its Indicadores Demograficos Basicos (INE, *Indicadores Demograficos Basicos: Metodologia*, pp. 4 and 9-10):

Usage

```
age_specific_fertility_rate(
  births_age_df,
  pop_df,
  age_min = 15L,
  age_max = 49L
)
```

Arguments

births_age_df Tibble as returned by `get_ine_births_by_age()`\$data (columns nuts3_code, province_name, year, age, female, total, and optionally age_group).

pop_df Population tibble as returned by `get_ine_population()`\$data (columns nuts3_code, year, age, female), January-1 stocks.

age_min, age_max Integer bounds of the reproductive age span (default 15-49).

Details

- **Exposure** is the mean annual female population, the average of the January-1 stocks of years t and $t + 1$. If the $t + 1$ stock is not in `pop_df`, the t stock is used and the row is flagged with `is_boundary_year = TRUE` (with a warning).
- **Out-of-range births** are folded into the boundary ages: births to mothers younger than `age_min` (including INE's "under 15" group, coded `age = NA`, `age_group = "under15"`) are added to age `age_min`, and births to mothers older than `age_max` (INE's "50 and over") to age `age_max`. No births are dropped.

Value

A tibble with `nuts3_code`, `province_name`, `year`, `age`, `births`, `women` (mean annual female population), `asfr` (births per woman), `asfr_female` (female births per woman, for [gross_reproduction_rate\(\)](#) and [net_reproduction_rate\(\)](#)), `asfr_per_1000` ($1000 * asfr$, for display), and `is_boundary_year`.

Examples

```
births_age <- tibble::tibble(
  nuts3_code = "ES111", province_name = "A Coruna", year = 2023,
  age = c(20, 30), female = c(10, 25), total = c(20, 50)
)
pop <- tibble::tibble(
  nuts3_code = "ES111", year = rep(2023:2024, each = 2), age = c(20, 30, 20, 30),
  female = c(2000, 2500, 2100, 2400)
)
age_specific_fertility_rate(births_age, pop)
```

aging_index	<i>Aging index</i>
-------------	--------------------

Description

Computes the aging index (elderly per 100 children) per province and year from age-disaggregated population data. Requires an age breakdown, so it operates on `get_ine_population()`'s output, not `get_ine_demog()`'s `population_total` indicator.

Usage

```
aging_index(pop_df, young_max = 14L, old_min = 65L)
```

Arguments

pop_df	Population tibble as returned by <code>get_ine_population()</code> \$data (columns nuts3_code, province_name, year, age, total).
young_max	Integer, the maximum age counted as "young" (default 14, i.e. ages 0-14).
old_min	Integer, the minimum age counted as "old" (default 65).

Value

A tibble with nuts3_code, province_name, year, aging_index.

Examples

```
pop <- tibble::tibble(
  nuts3_code = "ES111", province_name = "A Coruna", year = 2023,
  age = c(0, 20, 70), total = c(100, 300, 150)
)
aging_index(pop)
```

andreev_kingkade_a0	<i>Andreev-Kingkade a0 (mean age at death in the first year of life)</i>
---------------------	--

Description

Period (m0-based) formulas of Andreev and Kingkade (2015) as tabulated in HMD Methods Protocol V6, Table 3. Each interval is closed at its lower bound.

Usage

```
andreev_kingkade_a0(m0, sex = c("female", "male"))
```

Arguments

m0	Central death rate at age 0 (a single number).
sex	"female" or "male" (case-insensitive).

Details

Sex	m0 range	a0
Male	[0, 0.02300)	0.14929 - 1.99545 m0
Male	[0.02300, 0.08307)	0.02832 + 3.26021 m0
Male	[0.08307, Inf)	0.29915
Female	[0, 0.01724)	0.14903 - 2.05527 m0
Female	[0.01724, 0.06891)	0.04667 + 3.88089 m0
Female	[0.06891, Inf)	0.31411

Value

Numeric a0 value, NA if m0 is NA.

References

Andreev, E. M. and Kingkade, W. W. (2015). Average age at death in infancy and infant mortality level: Reconsidering the Coale-Demeny formulas at current levels of low mortality. *Demographic Research* 33(13): 363-390. doi:[10.4054/DemRes.2015.33.13](https://doi.org/10.4054/DemRes.2015.33.13)

Examples

```
andreev_kingkade_a0(0.004, "female")
andreev_kingkade_a0(0.15, "male")
```

birth_death_ratio	<i>Birth-to-death ratio</i>
-------------------	-----------------------------

Description

Computes the birth-to-death ratio (live births per death) per geography and year. Unlike `age_dependency_ratio()/aging_in_sex_ratio()`, this needs no age breakdown, so it operates directly on `get_ine_demog()`'s totals (System A) rather than `get_ine_population()` (System B) — fetch both `births_total` and `deaths_total` in one call and pass the result straight through.

Usage

```
birth_death_ratio(df)
```

Arguments

df	Output of <code>get_ine_demog(indicator = c("births_total", "deaths_total"))</code> (columns GEOID, NAME, year, births_total, deaths_total).
----	--

Value

A tibble with GEOID, NAME, year, birth_death_ratio. A value of 2 means 2 live births per death; 0.5 means 1 birth per 2 deaths.

Examples

```
df <- tibble::tibble(
  GEOID = c("15", "28"), NAME = c("A Coruna", "Madrid"), year = 2023,
  births_total = c(3000, 30000), deaths_total = c(6000, 25000)
)
birth_death_ratio(df)
```

build_abridged_life_table

Build an abridged (5-year age group) period life table

Description

Constructs an abridged period life table (age groups "00-04", "05-09", ..., "95-99", "100+") independently from observed grouped central death rates. It is a separate estimate, not an abridgement of the single-year table from `build_life_tables()`: it uses no Kannisto smoothing, and its open interval is 100+ rather than 110+, so the two tables' life expectancies differ slightly by construction.

Usage

```
build_abridged_life_table(mx_1x1, mx_5x1, sex = c("female", "male"))
```

Arguments

mx_1x1	tibble with columns age (single years, at least 0:4), mx, for one year and one sex - see compute_death_rates() 's mx_1x1 output, filtered to one province/year/sex.
mx_5x1	tibble with columns age_group ("00-04", "05-09", ..., "100+"), mx, for the same year and sex - see compute_death_rates() 's mx_5x1 output, filtered the same way.
sex	"female" or "male" - selects the Andreev-Kingkade a0 branch for the youngest group, same as build_life_table() .

Details

Closed groups from age 5 use Greville's nax with the Chiang conversion $nqx = n \cdot nm_x / (1 + (n - nax) \cdot nm_x)$ and $nLx = n \cdot l(x+n) + nax \cdot ndx$ (Preston, Heuveline & Guillot 2001, Box 3.1), falling back to a constant hazard ($nqx = 1 - \exp(-n \cdot nm_x)$, $nLx = ndx / nm_x$) where Greville's slope term is undefined. Both keep $nm_x = ndx / nLx$ exactly. The open interval has $qx = 1$, $Lx = lx / mx$. Complements [build_life_table\(\)](#)'s single-year (1x1) tables - use this when comparing against other agencies' published abridged tables, or when only grouped-age data is available. The youngest group ("00-04") is the one exception to using mx_5x1 alone: it is built from an exact single-year sub-table using mx_1x1's Andreev-Kingkade a0 (see [andreev_kingkade_a0\(\)](#)), avoiding the external $nax(0-4)$ regression a from-mx_5x1-alone method would otherwise need for that interval's sharp infant-mortality gradient.

Value

tibble: age_group, age_start, n (interval width, NA for the open interval), mx, ax, qx, lx, dx, Lx, Tx, ex.

Examples

```
mx1 <- data.frame(age = 0:4, mx = c(0.004, 0.0003, 0.0002, 0.0002, 0.0002))
mx5 <- data.frame(
  age_group = c("00-04", "05-09", "100+"), mx = c(0.0006, 0.0001, 0.35)
)
build_abridged_life_table(mx1, mx5, "female")
```

build_abridged_life_tables

Build abridged period life tables for every province

Description

Constructs female, male, and both-sex abridged (5-year age group) period life tables for every province and year present in mx_5x1, from [compute_death_rates\(\)](#)'s mx_1x1/mx_5x1 output. See [build_abridged_life_table\(\)](#) for the method; [build_life_tables\(\)](#) for the single-year (1x1) equivalent this complements.

Usage

```
build_abridged_life_tables(mx_1x1, mx_5x1)
```

Arguments

`mx_1x1` Output of the `mx_1x1` element of `compute_death_rates()`.
`mx_5x1` Output of the `mx_5x1` element of `compute_death_rates()`.

Value

`list(fltper, mltper, bltper, qc)`: each a tibble with `nuts3_code`, `province_name`, `year`, `age_group`, `age_start`, `n`, `mx`, `ax`, `qx`, `lx`, `dx`, `Lx`, `Tx`, `ex`; `qc` is a named list of `validate_abridged_life_table()` results.

Examples

```
mx_1x1 <- tibble::tibble(
  nuts3_code = "ES111", province_name = "A Coruna", year = 2023,
  age = 0:4, mx_female = c(0.004, 0.0003, 0.0002, 0.0002, 0.0002),
  mx_male = c(0.005, 0.0004, 0.0003, 0.0003, 0.0003),
  mx_total = c(0.0045, 0.00035, 0.00025, 0.00025, 0.00025)
)
mx_5x1 <- tibble::tibble(
  nuts3_code = "ES111", province_name = "A Coruna", year = 2023,
  age_group = c("00-04", "100+"),
  mx_female = c(0.0006, 0.35), mx_male = c(0.0008, 0.4), mx_total = c(0.0007, 0.38)
)
alt <- build_abridged_life_tables(mx_1x1, mx_5x1)
alt$fltper
```

<code>build_life_table</code>	<i>Build a period life table from a mortality schedule</i>
-------------------------------	--

Description

Standard life-table recursion from a complete schedule of central death rates, per HMD Methods Protocol V6: Andreev-Kingkade a_0 at age 0, $ax = 0.5$ at every other closed age, and an open final interval with $qx = 1$, $ax = 1/mx$, $Lx = lx/mx$. No smoothing is applied; use `build_life_tables()` for Kannisto old-age smoothing of observed data.

Usage

```
build_life_table(mx_df, sex = c("female", "male"), a0 = NULL)
```

Arguments

<code>mx_df</code>	Data frame with columns <code>age</code> and <code>mx</code> for one year and one sex. Ages must be unique, contiguous single years starting at 0; the last age is treated as the open interval. Rates must be finite and non-negative, and the open-interval rate positive.
<code>sex</code>	"female" or "male", selecting the Andreev-Kingkade branch.
<code>a0</code>	Optional override for <code>a0</code> (used for combined-sex tables).

Value

tibble: `age`, `mx`, `qx`, `ax`, `lx`, `dx`, `Lx`, `Tx`, `ex` (radix 10 = 100000).

Examples

```
mx <- data.frame(age = 0:100, mx = 0.0003 * exp(0.07 * (0:100)))
build_life_table(mx, "female")
```

<code>build_life_tables</code>	<i>Build period life tables for every province</i>
--------------------------------	--

Description

Constructs female, male, and combined-sex single-year period life tables (ages 0 to 110+) for every province and year in `mx_1x1`.

Usage

```
build_life_tables(mx_1x1, kannisto_age = NULL, fit_min = KANNISTO_FIT_MIN)
```

Arguments

<code>mx_1x1</code>	The <code>mx_1x1</code> element of <code>compute_death_rates()</code> (needs the <code>mx_*</code> , <code>d_*</code> , and <code>e_*</code> columns).
<code>kannisto_age</code>	Optional fixed replacement age Y (an integer in 80-100) overriding the HMD 100-deaths rule; for sensitivity analysis.
<code>fit_min</code>	First age of the Kannisto fitting window (default 80, as in HMD; the window ends at 99). For sensitivity analysis.

Value

A list:

- `fltp`, `mltp`, `bltp`: tibbles with `nuts3_code`, `province_name`, `year`, `age`, `mx`, `qx`, `ax`, `lx`, `dx`, `Lx`, `Tx`, `ex`.
- `qc`: tibble with one row per table built (`nuts3_code`, `year`, `sex`, `kannisto_age = Y`, `passed`, `issues`).
- `failed`: tibble of withheld tables (`nuts3_code`, `province_name`, `year`, `sex`, `reason`).

Method

Follows HMD Methods Protocol V6, Section 7.1:

- Observed rates are used below the replacement age Y , the lowest age from 80 with at most 100 female or 100 male deaths, capped at 95 (the same Y for both sexes).
- From Y upward, rates come from a Kannisto model fitted to deaths and exposures at ages 80-99 by Poisson maximum likelihood, with both parameters constrained to be non-negative so smoothed rates cannot fall with age.
- Combined-sex rates at ages $Y+$ weight the smoothed sex-specific rates by a smoothed female share of exposure; combined-sex a_0 is the death-weighted average of the sex-specific Andreev-Kingkade values.

Deviations from HMD V6, all forced by the INE inputs: (i) exposure uses an even Lexis-triangle split because INE deaths are not classified by cohort (see `compute_exposure()`); (ii) the Kannisto fit uses ages 80-99 because INE's single-year detail ends at an open interval 100+, whereas HMD fits to 80-110+; (iii) no birth-by-month exposure correction.

Failure behaviour

A province-year whose input lacks finite rates and exposures at every single age 0-100 is not tabulated: its three tables are withheld and the reason is reported in `failed`. This covers INE releases whose population or deaths are top-coded below age 100 (for example, some historical years for Ceuta and Melilla).

Examples

```
age <- 0:100
e <- 1e5
mx <- 0.0003 * exp(0.07 * age)
mx_1x1 <- tibble::tibble(
  nuts3_code = "ES111", province_name = "A Coruna", year = 2023, age = age,
  mx_female = mx, mx_male = 1.2 * mx, mx_total = 1.1 * mx,
  d_female = mx * e, d_male = 1.2 * mx * e, d_total = 2.2 * mx * e,
  e_female = e, e_male = e, e_total = 2 * e
)
lt <- build_life_tables(mx_1x1)
lt$fltper
```

compute_death_rates	<i>Compute central death rates for every province</i>
---------------------	---

Description

Computes 1x1 (single-year age/period), 5x1 (5-year age group), and age-standardised (ESP 2013) death rates for every province present in both deaths and exposure, per SHMD Protocol Section 12, Step 5.

Usage

```
compute_death_rates(deaths, exposure)
```

Arguments

deaths Output of the data_provinces element of `get_ine_deaths()`.

exposure Output of the data element of `compute_exposure()`.

Value

```
list(mx_1x1, mx_5x1, asdr, qc):
```

- **mx_1x1**: nuts3_code, province_name, year, age, central death rates mx_female, mx_male, mx_total, and the deaths (d_*) and exposures (e_*) they come from (needed by `build_life_tables()`).
- **mx_5x1**: the same by five-year group (age_group), pooled as `sum(deaths) / sum(exposure)`.
- **asdr**: age-standardised death rates per 100,000 (European Standard Population 2013; the 95+ weight of 200 is spread evenly over ages 95-99 and 100+). NA unless all ages 0-100 have finite rates.
- **qc**: output of `validate_death_rates()` on **mx_1x1**.

Missing data

INE's age-specific deaths table omits cells with zero deaths, so an age missing from a province-year that is otherwise present is treated as a structural zero. An explicit NA count (unavailable or suppressed and not recoverable) is kept as NA and propagates to the rate, the grouped rate, and the ASDR, and makes `validate_death_rates()` fail. A province-year with exposure but no death records at all is unavailable, not zero: it is excluded with a warning.

Examples

```
deaths <- tibble::tibble(
  nuts3_code = "ES111", province_name = "A Coruna", year = 2023,
  age = c(0, 1), female = c(1, 0), male = c(1, 1), total = c(2, 1)
)
exposure <- tibble::tibble(
  nuts3_code = "ES111", province_name = "A Coruna", year = 2023,
  age = c(0, 1), female = c(500, 490), male = c(510, 505), total = c(1010, 995)
)
rates <- compute_death_rates(deaths, exposure)
rates$mx_1x1
rates$asdr
```

compute_exposure	<i>Compute exposure-to-risk for every province</i>
------------------	--

Description

Computes $E(x,t) = 1/2[P(x,t) + P(x,t+1)] + 1/6[D_L(x,t) - D_U(x,t)]$ (HMD Methods Protocol V6, Eq. 57) for every province present in both population and deaths, where D_L and D_U are deaths in the lower (cohort born in $t - x$) and upper (cohort born in $t - x - 1$) Lexis triangles.

Usage

```
compute_exposure(population, deaths)
```

Arguments

population	Output of the data element of get_ine_population() .
deaths	Output of the data_provinces element of get_ine_deaths() .

Details

INE's death tables are not classified by birth cohort. Unless deaths carries a cohort t column, deaths are split evenly between the two triangles, the correction term is zero, and exposure is the mean of the two January-1 populations. This is an adaptation of the HMD protocol, which splits 1x1 deaths by regression (Appendix A) and corrects for the monthly distribution of births (Appendix E); its effect is quantified in the package's validation study (see [reproducibility/](#)).

If $P(x, t+1)$ is unavailable for a year that is kept, exposure falls back to $P(x, t)$ and the row is flagged with `is_boundary_year = TRUE`.

Death registration lags population estimates by about a year, so population commonly includes a most-recent year (e.g. a Jan-1 stock snapshot) with no corresponding rows anywhere in deaths yet. That year is still used as the $P(x, t+1)$ boundary for computing the *previous* year's exposure, but is **not** included in the returned exposure rows itself — treating an entirely-absent year as zero deaths (rather than missing data) would mechanically produce zero mortality for that year, and downstream a nonsensical inflated life expectancy.

Value

`list(data, qc)`: `data` is a tibble with columns `nuts3_code`, `province_name`, `year`, `age`, `female`, `male`, `total (exposure)`, `is_boundary_year`, `is_missing_source_pop`; `qc` is the output of [validate_exposure\(\)](#).

Examples

```
population <- tibble::tibble(
  nuts3_code = "ES111", province_name = "A Coruna",
  year = c(2022, 2023), age = 0,
  female = c(100, 105), male = c(105, 110), total = c(205, 215)
)
deaths <- tibble::tibble(
```

```

nuts3_code = "ES111", province_name = "A Coruna",
year = c(2022, 2023), age = 0,
female = c(1, 1), male = c(1, 2), total = c(2, 3)
)
compute_exposure(population, deaths)

```

crude_birth_rate	<i>Crude birth rate</i>
------------------	-------------------------

Description

Computes the crude birth rate (births per 1,000 population) per province and year, joining [get_ine_births\(\)](#) and [get_ine_population\(\)](#) output.

Usage

```
crude_birth_rate(births_df, pop_df)
```

Arguments

births_df	Births tibble as returned by get_ine_births() \$data (columns nuts3_code, province_name, year, total).
pop_df	Population tibble as returned by get_ine_population() \$data (columns nuts3_code, year, age, total).

Details

This is a *crude* birth rate (total births / total population), **not** a total fertility rate (TFR). [get_ine_births\(\)](#) itself has no age-of-mother breakdown, so `crude_birth_rate()` cannot compute a TFR on its own — for a true TFR, use [get_ine_births_by_age\(\)](#) with [age_specific_fertility_rate\(\)/total_fertility_rate\(\)](#) instead. Do not substitute `crude_birth_rate()` for TFR in fertility analysis.

Value

A tibble with nuts3_code, province_name, year, cbr.

Examples

```

births <- tibble::tibble(
  nuts3_code = "ES111", province_name = "A Coruna", year = 2023, total = 100
)
pop <- tibble::tibble(
  nuts3_code = "ES111", year = 2023, age = c(0, 1), total = c(5000, 5000)
)
crude_birth_rate(births, pop)

```

crude_death_rate	<i>Crude death rate</i>
------------------	-------------------------

Description

Computes the crude death rate (deaths per 1,000 population) per province and year, joining `get_ine_deaths()` and `get_ine_population()` output. The symmetric counterpart to `crude_birth_rate()` — see `rate_of_natural_increase()` to combine the two.

Usage

```
crude_death_rate(deaths_df, pop_df)
```

Arguments

deaths_df	Deaths tibble as returned by <code>get_ine_deaths()</code> \$data_provinces (columns nuts3_code, province_name, year, age, total). Unlike <code>crude_birth_rate()</code> 's births_df, this is age-specific, so it is summed over age internally before computing the rate.
pop_df	Population tibble as returned by <code>get_ine_population()</code> \$data (columns nuts3_code, year, age, total).

Value

A tibble with nuts3_code, province_name, year, cdr.

Examples

```
deaths <- tibble::tibble(  
  nuts3_code = "ES111", province_name = "A Coruna", year = 2023,  
  age = c(0, 1), total = c(1, 49)  
)  
pop <- tibble::tibble(  
  nuts3_code = "ES111", year = 2023, age = c(0, 1), total = c(5000, 5000)  
)  
crude_death_rate(deaths, pop)
```

decompose_life_expectancy	<i>Decompose a difference in life expectancy at birth by age</i>
---------------------------	--

Description

Attributes the difference in life expectancy at birth (e_0) between two life tables to age-specific contributions, using either Arriaga's (1984) or Pollard's (1988) method. Arriaga's is an exact discrete decomposition: `sum(contribution)` recovers $e_2(0) - e_1(0)$ exactly. Pollard's is exact in continuous time; here each closed single-year interval is integrated with the midpoint rule and the open interval exactly under its constant hazard, so `sum(contribution)` differs from $e_2(0) - e_1(0)$ by a small discretisation residual. The residual is returned as an attribute so it can be reported and checked against a tolerance; treat Arriaga's method (the default) as the primary result and Pollard's as a cross-check. Use this to answer "how much of the life-expectancy gap between province A and B (or between year Y1 and Y2) comes from mortality at each age?" - complementing `life_expectancy_summary()`/`life_expectancy()`, which report e_0/e_{65} but don't explain why two values differ.

Usage

```
decompose_life_expectancy(lt1, lt2, method = c("arriaga", "pollard"))
```

Arguments

lt1	A single life table (the "before"/reference table) - one province-year-sex slice of <code>build_life_tables()</code> 's <code>fltper</code> , <code>mltper</code> , or <code>bltper</code> (or <code>build_life_table()</code> 's direct output). Must have one row per age, sorted or unsorted, with columns age, mx, lx, Lx, Tx, ex.
lt2	The "after"/comparison life table, same shape as lt1, over the <i>same set of ages</i> as lt1.
method	"arriaga" (default) or "pollard".

Value

A tibble with age, contribution (years of the $e_2(0) - e_1(0)$ gap attributable to mortality differences at that age; positive means that age group contributed to a *gain* from lt1 to lt2). Attributes `e0_difference` (the actual $e_2(0) - e_1(0)$) and `residual` ($e_0_difference - \text{sum}(\text{contribution})$, zero up to rounding for Arriaga).

Examples

```
age <- 0:100
lt1 <- build_life_table(
  data.frame(age = age, mx = 0.0004 * exp(0.075 * age)), "female"
)
lt2 <- build_life_table(
  data.frame(age = age, mx = 0.0003 * exp(0.070 * age)), "female"
)
decomp <- decompose_life_expectancy(lt1, lt2)
sum(decomp$contribution)
lt2$ex[1] - lt1$ex[1]
```

download_ine_data	<i>Download SHMD pipeline data to a local folder</i>
-------------------	--

Description

Runs the requested stage(s) of the SHMD (Spanish subnational Human Mortality Database) protocol pipeline — retrieval of province-level births/deaths/population from INE, exposure-to-risk, central death rates, and period life tables — and writes the results into `out_dir` as `.csv` and/or HMD-format `.txt` files, so they can be inspected, shared, or fed into other HMD-compatible tooling without staying in the R session.

Usage

```
download_ine_data(
  out_dir,
  stages = c("births", "deaths", "population", "exposure", "mx", "life_tables"),
  format = c("csv", "txt"),
  n_periods = 30
)
```

Arguments

<code>out_dir</code>	Directory to write into (created if it doesn't exist).
<code>stages</code>	Character vector of stages to include. One or more of "births", "deaths", "population", "exposure", "mx", "life_tables". Default: all of them.
<code>format</code>	Character vector, one or both of "csv" and "txt". "csv" writes one combined file per data table; "txt" writes HMD-format files, one per province. Default: both.
<code>n_periods</code>	Number of most recent years to fetch for the births/deaths/population retrieval stages.

Details

Later stages depend on earlier ones (exposure needs population and deaths; mx needs deaths and exposure; life_tables needs mx). Requesting a later stage automatically fetches/computes and writes its dependencies too, since they were already retrieved along the way.

Value

Invisibly, a list with the in-memory results of every stage that was run (births, deaths, population, exposure, death_rates, life_tables, each NULL if not run) and files, a character vector of every path written.

Examples

```
## Not run:
# Not run: requires live network access to the INE API, and writes files
# to disk.
# Everything, both formats, into ./ine_data
download_ine_data("ine_data")

# Just births and deaths, CSV only
download_ine_data("ine_data", stages = c("births", "deaths"), format = "csv")

# Full pipeline through life tables
download_ine_data("ine_data", stages = "life_tables", n_periods = 40)

## End(Not run)
```

general_fertility_rate

General fertility rate

Description

Computes the general fertility rate (births per 1,000 women of reproductive age) per province and year, joining [get_ine_births\(\)](#) and [get_ine_population\(\)](#) output.

Usage

```
general_fertility_rate(births_df, pop_df, age_min = 15L, age_max = 49L)
```

Arguments

births_df	Births tibble as returned by get_ine_births() \$data (columns nuts3_code, province_name, year, total).
pop_df	Population tibble as returned by get_ine_population() \$data (columns nuts3_code, year, age, female).
age_min	Integer, the youngest age counted as reproductive-age (default 15).
age_max	Integer, the oldest age counted as reproductive-age (default 49).

Details

GFR improves on [crude_birth_rate\(\)](#) by dividing births by the female population actually at risk of childbearing (age age_min-age_max, default 15-49) instead of the total population — this removes the distortion [crude_birth_rate\(\)](#) suffers when two provinces have different age/sex structures (e.g. one with proportionally more elderly residents) despite similar underlying fertility behavior.

GFR is still **not** a total fertility rate (TFR): it is a single aggregate rate over all reproductive-age women, not an age-specific schedule. For a true TFR, use [get_ine_births_by_age\(\)](#) with [age_specific_fertility_rate\(\)/total_fertility_rate\(\)](#) instead.

Value

A tibble with nuts3_code, province_name, year, gfr.

Examples

```
births <- tibble::tibble(
  nuts3_code = "ES111", province_name = "A Coruna", year = 2023, total = 100
)
pop <- tibble::tibble(
  nuts3_code = "ES111", year = 2023, age = c(10, 25, 40, 60),
  female = c(2000, 2500, 2500, 3000)
)
general_fertility_rate(births, pop)
```

get_ine_births	<i>Retrieve province-level births</i>
----------------	---------------------------------------

Description

Retrieves, cleans, and validates Spanish annual live-birth counts by province and sex from INE's Tempus3 JSON API, per the SHMD Protocol (Section 12, Step 1: "Birth Count Assembly"). Unlike [get_ine_demog\(\)](#) (which returns a Total-sex-only province count), this returns sex-disaggregated counts joined to NUTS-3 codes, suitable as an HMD-format Births input file - see [download_ine_data\(\)](#) to write it to disk.

Usage

```
get_ine_births(
  table_id = 6506,
  n_periods = 100,
  use_cache = TRUE,
  force = FALSE,
  cache_dir = NULL
)
```

Arguments

table_id	INE Tempus3 table ID. Default 6506, confirmed for "Nacimientos por lugar de residencia de la madre y sexo. Total nacional y provincias" (operation MNPN). Pass NULL to auto-discover.
n_periods	Number of most recent years to fetch.
use_cache	Logical (default TRUE). If a previous call already cached a result for this table_id/n_periods combination, return it directly instead of re-fetching from INE — this function's live fetch is one of the package's slowest. Set FALSE to always hit the network.
force	Logical (default FALSE). If TRUE, ignore any existing cache and re-fetch from INE, refreshing the cache afterwards.

cache_dir Directory for cached data. The default NULL caches in a per-session directory under `tempdir()`: repeated calls in the same session reuse the first download, but nothing persists afterwards. Pass a directory, e.g. `tools::R_user_dir("inedemogR", "cache")`, for a cache that persists across sessions. A cache stores the parsed result as `.rds`; refresh it with `force = TRUE`. Results carry a provenance attribute (`request`, retrieval time in UTC, API, package version).

Value

`list(data, qc)`: `data` is a tibble with columns `ine_code`, `nuts3_code`, `nuts2_code`, `province_name`, `year`, `female`, `male`, `total`; `qc` is the output of `validate_births()`.

Examples

```
## Not run:
# Not run: requires live network access to the INE API.
births <- get_ine_births(n_periods = 30)
births$data
births$qc$issues

# Re-fetch even if a cached copy exists:
births <- get_ine_births(n_periods = 30, force = TRUE)

## End(Not run)
```

`get_ine_births_by_age` Retrieve province-level births by age of mother

Description

Retrieves, cleans, and validates Spanish annual live-birth counts by province, single year of age of the mother (15–49, plus the two open intervals `under15`/`50plus`), and sex of the newborn, from INE's raw Tempus3 JSON API. Unlike `get_ine_births()` (which has no age-of-mother breakdown), this is the data source needed for age-specific fertility rates - see `age_specific_fertility_rate()`, `total_fertility_rate()`, `mean_age_at_childbearing()`, `gross_reproduction_rate()`, and `net_reproduction_rate()`.

Usage

```
get_ine_births_by_age(
  table_id = 6508,
  n_periods = 100,
  use_cache = TRUE,
  force = FALSE,
  cache_dir = NULL
)
```

Arguments

table_id	INE Tempus3 table ID. Default 6508, confirmed for "Nacimientos por lugar de residencia de la madre, sexo y edad de la madre. Total nacional y provincias" (operation MNPN).
n_periods	Number of most recent years to fetch. This table has ~6,000 series (province x age x newborn-sex), so fetches are slower than get_ine_births() 's; caching (see use_cache) matters more here.
use_cache	Logical (default TRUE). See get_ine_births() .
force	Logical (default FALSE). See get_ine_births() .
cache_dir	Directory for cached data. The default NULL caches in a per-session directory under <code>tempdir()</code> : repeated calls in the same session reuse the first download, but nothing persists afterwards. Pass a directory, e.g. <code>tools::R_user_dir("inedemogR", "cache")</code> , for a cache that persists across sessions. A cache stores the parsed result as <code>.rds</code> ; refresh it with <code>force = TRUE</code> . Results carry a provenance attribute (request, retrieval time in UTC, API, package version).

Value

`list(data, qc)`: `data` is a tibble with columns `ine_code`, `nuts3_code`, `nuts2_code`, `province_name`, `year`, `age` (integer, NA for the under15 group), `age_group` (character: "under15", "15".."49", "50plus"), `female`, `male`, `total` (births to mothers of that age, by sex of the newborn); `qc` is the output of [validate_births_by_age\(\)](#).

Examples

```
## Not run:
# Not run: requires live network access to the INE API.
births_age <- get_ine_births_by_age(n_periods = 10)
births_age$data

## End(Not run)
```

get_ine_deaths	<i>Retrieve province-level deaths</i>
----------------	---------------------------------------

Description

Retrieves, cleans, and validates Spanish annual death counts by province and sex from INE's Tempus3 JSON API, per the SHMD Protocol (Section 12, Step 1: "Death Count Assembly"). Fetches both an age-less table (for the national total and a national-vs-provincial reconciliation check) and an age-specific table (needed by [compute_exposure\(\)](#) / [compute_death_rates\(\)](#), which require $D(x,t)$, not just $D(t)$).

Usage

```
get_ine_deaths(
  table_id = 6545,
  age_table_id = 6547,
  n_periods = 100,
  use_cache = TRUE,
  force = FALSE,
  cache_dir = NULL
)
```

Arguments

<code>table_id</code>	INE table ID for the age-less (province + sex) series. Default 6545, confirmed for "Defunciones por lugar de residencia y sexo. Total nacional y provincias" (operation MNPD).
<code>age_table_id</code>	INE table ID for the age-specific series. Default 6547.
<code>n_periods</code>	Number of most recent years to fetch.
<code>use_cache</code>	Logical (default TRUE). If a previous call already cached a result for this <code>table_id/age_table_id/n_periods</code> combination, return it directly instead of re-fetching from INE — this function's live fetch (two tables) is one of the package's slowest. Set FALSE to always hit the network.
<code>force</code>	Logical (default FALSE). If TRUE, ignore any existing cache and re-fetch from INE, refreshing the cache afterwards.
<code>cache_dir</code>	Directory for cached data. The default NULL caches in a per-session directory under <code>tempdir()</code> : repeated calls in the same session reuse the first download, but nothing persists afterwards. Pass a directory, e.g. <code>tools::R_user_dir("inedemogR", "cache")</code> , for a cache that persists across sessions. A cache stores the parsed result as <code>.rds</code> ; refresh it with <code>force = TRUE</code> . Results carry a provenance attribute (request, retrieval time in UTC, API, package version).

Value

`list(data_provinces, data_national, qc, qc_age)`: `data_provinces` is age-specific (`ine_code`, `nuts3_code`, `nuts2_code`, `province_name`, `year`, `age`, `female`, `male`, `total`); `data_national` is Spain's age-less total.

Examples

```
## Not run:
# Not run: requires live network access to the INE API.
deaths <- get_ine_deaths(n_periods = 30)
deaths$data_provinces

# Re-fetch even if a cached copy exists:
deaths <- get_ine_deaths(n_periods = 30, force = TRUE)

## End(Not run)
```

get_ine_demog

Get INE Demographic Data

Description

Retrieves demographic data from INE via the official `ineapir::get_data_table()` API wrapper, and tidies it into a data frame with one row per geography x year and one column per indicator.

Usage

```
get_ine_demog(  
  indicator,  
  geo_level = NULL,  
  year = NULL,  
  region = NULL,  
  sex = "Total",  
  geometry = FALSE  
)
```

Arguments

<code>indicator</code>	Character vector of indicator codes (see <code>list_ine_indicators()</code>).
<code>geo_level</code>	Character, the geographic level to fetch. Must match the level at which every requested indicator is actually published (see <code>list_ine_indicators()</code>). If <code>NULL</code> (default), inferred from <code>indicator</code> .
<code>year</code>	Numeric or character, the year of data. Default (<code>NULL</code>) returns the latest available period only.
<code>region</code>	Optional character vector to subset by region name (regular expressions allowed, matched against the geography name).
<code>sex</code>	Character, one of "Total", "Hombres", "Mujeres".
<code>geometry</code>	Logical, join geometries from <code>get_ine_geo()</code> (default <code>FALSE</code>).

Details

Each indicator is mapped to a real INE table id via the `ine_variables` registry (see `list_ine_indicators()`). Different indicators are only available at different geographic granularities in INE's source tables (e.g. population is published by municipality, but births/deaths only down to province) — all requested indicators must share the same `geo_level`, or request them separately.

Value

A tidy tibble with columns `GEOID`, `NAME`, `year`, and one column per requested indicator; an `sf` object if `geometry = TRUE`.

Examples

```
## Not run:
# Not run: requires live network access to the INE API.
pop_data <- get_ine_demog(indicator = "population_total", year = 2023)
births_deaths <- get_ine_demog(
  indicator = c("births_total", "deaths_total"), year = 2023
)

## End(Not run)
```

get_ine_geo

Get INE Geographic Data

Description

Retrieves spatial geometries for INE geographic levels via the [mapSpain](#) package, which sources boundaries from Instituto Geografico Nacional / GISCO. Geometries are returned with a GEOID column that matches the geographic codes returned by [get_ine_demog\(\)](#), so the two can be joined directly.

Usage

```
get_ine_geo(
  geo_level = c("municipality", "province"),
  region = NULL,
  moveCAN = TRUE,
  can_gap_km = 60
)
```

Arguments

geo_level	Character, one of "municipality" or "province".
region	Optional character vector to subset by region name (regular expressions allowed).
moveCAN	Logical, shift the Canary Islands next to the mainland for compact national maps (default TRUE). Pass FALSE to keep their real geographic coordinates.
can_gap_km	Numeric, the gap in kilometers left between the shifted Canary Islands and the closest point on the mainland coast (default 60). Only used when moveCAN = TRUE. Smaller values move the islands closer.

Value

An sf object with columns GEOID, NAME, and geometry, projected to ETRS89 / UTM zone 30N (EPSG:25830). When moveCAN = TRUE and the shift was applied, an sfc rectangle marking the shifted islands' extent is attached as the "can_box" attribute (used by [plot_ine_map\(\)](#) to draw an inset frame).

Examples

```
## Not run:
# Not run: requires live network access to fetch boundaries via mapSpain.
prov_geo <- get_ine_geo(geo_level = "province")
mun_geo <- get_ine_geo(geo_level = "municipality", region = "Sevilla")

## End(Not run)
```

get_ine_population	<i>Retrieve province-level population by age and sex</i>
--------------------	--

Description

Retrieves, cleans, and validates Spanish January-1st provincial population estimates by single-year age and sex from INE's Padron Municipal Continuo, per the SHMD Protocol (Section 12, Step 3: "Population Estimates"). Covers 1996-present; pre-1996 years require the intercensal survival method applied to the 1981/1991 censuses, which is out of scope here.

Usage

```
get_ine_population(
  table_id = 56945,
  n_periods = 30,
  use_cache = TRUE,
  force = FALSE,
  cache_dir = NULL
)
```

Arguments

table_id	INE table ID. Default 56945 ("Poblacion residente por fecha, sexo y edad (desde 1971)", provincial variant, operation ECP). Pass NULL to auto-discover.
n_periods	Number of most recent years to fetch.
use_cache	Logical (default TRUE). If a previous call already cached a result for this table_id/n_periods combination, return it directly instead of re-fetching from INE, since this function's live fetch (often via the slower CSV bulk-export fallback) is one of the package's slowest. Set FALSE to always hit the network.
force	Logical (default FALSE). If TRUE, ignore any existing cache and re-fetch from INE, refreshing the cache afterwards.
cache_dir	Directory for cached data. The default NULL caches in a per-session directory under tempdir(): repeated calls in the same session reuse the first download, but nothing persists afterwards. Pass a directory, e.g. tools::R_user_dir("inedemogR", "cache"), for a cache that persists across sessions. A cache stores the parsed result as .rds; refresh it with force = TRUE. Results carry a provenance attribute (request, retrieval time in UTC, API, package version).

Details

Some province x age x sex population tables are too large for INE's JSON API and are rejected outright; this function automatically falls back to INE's full CSV bulk export in that case (a larger download, but with no series-count limit).

Value

`list(data, qc)`: `data` is a tibble with columns `ine_code`, `nuts3_code`, `nuts2_code`, `province_name`, `year`, `age`, `female`, `male`, `total`; `qc` is the output of `validate_population()`.

Examples

```
## Not run:
# Not run: requires live network access to the INE API.
pop <- get_ine_population(n_periods = 10)
pop$data

# Re-fetch even if a cached copy exists:
pop <- get_ine_population(n_periods = 10, force = TRUE)

## End(Not run)
```

gross_reproduction_rate

Gross reproduction rate (GRR)

Description

Sum of `age_specific_fertility_rate()`'s `asfr_female` (female births per woman): expected daughters per woman, ignoring mortality. Uses INE's births by sex of the newborn directly rather than scaling the TFR by an assumed sex ratio at birth.

Usage

```
gross_reproduction_rate(asfr_df)
```

Arguments

`asfr_df` Output of `age_specific_fertility_rate()`.

Value

A tibble with `nuts3_code`, `province_name`, `year`, `grr` (daughters per woman).

Examples

```
asfr <- tibble::tibble(
  nuts3_code = "ES111", province_name = "A Coruna", year = 2023,
  age = c(20, 30), asfr = c(0.03, 0.08), asfr_female = c(0.015, 0.04)
)
gross_reproduction_rate(asfr)
```

ine_variables	<i>INE demographic indicator reference table</i>
---------------	--

Description

A registry mapping indicator codes used throughout inedemogR to the real INE table each is retrieved from via `ineapir::get_data_table()`.

Usage

```
ine_variables
```

Format

A tibble with 3 rows and 6 variables:

indicator Indicator code, e.g. "population_total".

name Short human-readable name.

description Longer description of what the indicator measures.

id_table INE idTable identifier, or NA if not yet wired to a live table.

geo_var Name of the geographic dimension column returned by `ineapir::get_data_table(..., metanames = TRUE)` for this table.

geo_level Geographic granularity the table is published at ("municipality" or "province").

Source

Instituto Nacional de Estadística (INE), "fenomenos demograficos".

infant_mortality_rate *Infant mortality rate*

Description

Computes the infant mortality rate (deaths under age 1 per 1,000 live births) per province and year, joining `get_ine_deaths()` and `get_ine_births()` output.

Usage

```
infant_mortality_rate(deaths_df, births_df)
```

Arguments

deaths_df	Deaths tibble as returned by <code>get_ine_deaths()</code> \$data_provinces (columns nuts3_code, province_name, year, age, total).
births_df	Births tibble as returned by <code>get_ine_births()</code> \$data (columns nuts3_code, year, total).

Details

This is the standard demographic IMR: infant deaths in a year divided by live births *in that same year* (the birth cohort those deaths are drawn from), not by population — a different denominator convention from `crude_death_rate()`. It is closely related to, but not identical to, q_0 (probability of dying before age 1) in `build_life_table()`'s output: q_0 is derived from the exposure-based central death rate m_0 via the Andreev-Kingkade a_0 (per HMD Methods Protocol V6), while IMR here uses the simpler, more standard deaths/births ratio directly. The two will usually be close but need not match exactly.

Value

A tibble with nuts3_code, province_name, year, imr.

Examples

```
deaths <- tibble::tibble(
  nuts3_code = "ES111", province_name = "A Coruna", year = 2023,
  age = c(0, 1, 65), total = c(3, 1, 40)
)
births <- tibble::tibble(nuts3_code = "ES111", year = 2023, total = 1000)
infant_mortality_rate(deaths, births)
```

life_expectancy	<i>Life expectancy at birth and at age 65, for one province</i>
-----------------	---

Description

Convenience wrapper for a single province: builds a period life table (Andreev-Kingkade a0, Kannisto old-age smoothing, per HMD Methods Protocol V6) from already-computed central death rates and extracts life expectancy at birth (e0) and at age 65 (e65) for every year present. Operates on `compute_death_rates()`'s `mx_1x1` output directly — data already retrieved/computed via the mortality pipeline — the same way `plot_lexis_diagram()` does, rather than requiring `build_life_tables()` to be run for every province first and `life_expectancy_summary()` applied afterwards.

Usage

```
life_expectancy(mx_df, province, sex = c("total", "female", "male"))
```

Arguments

<code>mx_df</code>	Output of the <code>mx_1x1</code> element of <code>compute_death_rates()</code> (rates <code>mx_*</code> , deaths <code>d_*</code> , and exposures <code>e_*</code> for all three sexes, which <code>build_life_tables()</code> needs for Kannisto smoothing).
<code>province</code>	Character, a province name (regular expressions allowed, matched against <code>province_name</code> — same convention as <code>province</code> in <code>plot_lexis_diagram()</code>). Must match exactly one province.
<code>sex</code>	Character, one of "total", "female", "male".

Value

A tibble with `nuts3_code`, `province_name`, `year`, `e0`, `e65`, `sex`.

Examples

```
age <- 0:100
e <- 1e5
m <- 0.0003 * exp(0.07 * age)
mx <- tibble::tibble(
  nuts3_code = "ES111", province_name = "A Coruna", year = 2023, age = age,
  mx_female = m, mx_male = 1.2 * m, mx_total = 1.1 * m,
  d_female = m * e, d_male = 1.2 * m * e, d_total = 2.2 * m * e,
  e_female = e, e_male = e, e_total = 2 * e
)
life_expectancy(mx, province = "A Coruna", sex = "female")
```

life_expectancy_summary
Life expectancy summary

Description

Extracts life expectancy at birth (e0) and at age 65 (e65) per province and year from a `build_life_tables()` period life table. Feeds `map_life_expectancy()`, which bridges this summary with `get_ine_geo()`'s province geometries.

Usage

```
life_expectancy_summary(lt_df, sex = c("female", "male", "both"))
```

Arguments

lt_df	One of <code>build_life_tables()</code> 's <code>fltper</code> , <code>mltper</code> , or <code>bltper</code> tibbles (columns <code>nuts3_code</code> , <code>province_name</code> , <code>year</code> , <code>age</code> , <code>ex</code>).
sex	Character label to attach to the output ("female", "male", or "both") — purely descriptive, matching which life table (<code>fltper</code> / <code>mltper</code> / <code>bltper</code>) was passed in.

Value

A tibble with `nuts3_code`, `province_name`, `year`, `e0`, `e65`, `sex`.

Examples

```
lt <- tibble::tibble(
  nuts3_code = "ES111", province_name = "A Coruna", year = 2023,
  age = c(0, 65), ex = c(86.97, 20.5)
)
life_expectancy_summary(lt, sex = "female")
```

list_ine_indicators *List Available INE Indicators*

Description

Returns a data frame of available demographic indicators.

Usage

```
list_ine_indicators()
```

Value

A data frame with indicator codes, names, and descriptions.

Examples

```
list_ine_indicators()
```

map_indicator	<i>Map any indicator by province or municipality</i>
---------------	--

Description

General-purpose choropleth: joins a tidy indicator tibble (keyed by GEOID, matching `get_ine_geo()`'s output — e.g. `get_ine_demog()`'s output already has it) onto province or municipality geometry and renders it, either as a binned/discrete-legend map (the default, matching the classic "N provinces above/below a threshold" style of choropleth) or a continuous gradient. `map_life_expectancy()` is a thin wrapper around this function for System B's life-table output.

Usage

```
map_indicator(
  df,
  value_col,
  geo_level = c("province", "municipality"),
  region = NULL,
  binned = TRUE,
  breaks = NULL,
  palette = if (binned) "PiYG" else "D",
  moveCAN = TRUE,
  can_gap_km = 60,
  legend_title = NULL,
  title = NULL
)
```

Arguments

df	A tibble with a GEOID column (matching <code>get_ine_geo()</code> 's GEOID for the requested <code>geo_level</code>) and <code>value_col</code> .
value_col	Character, the name of the numeric column to map.
geo_level	Character, one of "province" or "municipality".
region	Optional character vector to subset the geometry by region name (regular expressions allowed). See <code>get_ine_geo()</code> .
binned	Logical (default TRUE). If TRUE, uses a discrete, binned color scale (<code>ggplot2::scale_fill_fermenter()</code> — a fixed number of color bands with a legend showing each band's range, matching the classic choropleth style. If FALSE, uses a continuous gradient (<code>ggplot2::scale_fill_viridis_c()</code> by default).
breaks	Numeric vector of bin edges when <code>binned = TRUE</code> . If NULL (default), computed automatically via <code>pretty()</code> .

palette	Character, a RColorBrewer palette name when binned = TRUE (default "PiYG", a pink-to-green diverging palette well suited to ratios centered on 1) or a viridis option letter when binned = FALSE (default "D").
moveCAN	Logical, shift the Canary Islands next to the mainland (default TRUE). See get_ine_geo() .
can_gap_km	Numeric, gap in km for the shifted Canary Islands (default 60). See get_ine_geo() .
legend_title	Optional legend title (defaults to value_col).
title	Optional plot title.

Value

A ggplot object.

Examples

```
## Not run:
# Not run: get_ine_geo() requires live network access to fetch boundaries.
pop_data <- get_ine_demog(indicator = "population_total", year = 2023)
map_indicator(pop_data, "population_total", geo_level = "province")

## End(Not run)
```

map_life_expectancy	<i>Map life expectancy by province</i>
---------------------	--

Description

Bridges System B's mortality pipeline ([build_life_tables\(\)](#) via [life_expectancy_summary\(\)](#)) with System A's spatial layer ([get_ine_geo\(\)](#)) to render a province-level choropleth of life expectancy at birth. A thin wrapper around [map_indicator\(\)](#) (a continuous gradient, since life expectancy has no natural discrete bins) that handles the nuts3_code -> GEOID bridge via province_lookup. See [plot_ine_map\(\)](#) for the analogous region-highlighting map built purely on [get_ine_geo\(\)](#).

Usage

```
map_life_expectancy(
  le_df,
  year,
  sex = "both",
  moveCAN = TRUE,
  can_gap_km = 60,
  title = NULL
)
```

Arguments

le_df	Output of <code>life_expectancy_summary()</code> (columns nuts3_code, year, e0, sex).
year	Numeric, the year to plot.
sex	Character, one of "female", "male", "both", matching the sex value in le_df to plot.
moveCAN	Logical, shift the Canary Islands next to the mainland (default TRUE). See <code>get_ine_geo()</code> .
can_gap_km	Numeric, gap in km for the shifted Canary Islands (default 60). See <code>get_ine_geo()</code> .
title	Optional plot title.

Value

A ggplot object.

Examples

```
## Not run:
# Not run: get_ine_geo() requires live network access to fetch province
# boundaries.
lt <- build_life_tables(rates$mx_1x1)
le <- life_expectancy_summary(lt$fltpcr, sex = "female")
map_life_expectancy(le, year = max(le$year), sex = "female")

## End(Not run)
```

mean_age_at_childbearing

Mean age at childbearing (MAC)

Description

ASFR-weighted mean of the mid-points $x + 0.5$ of the completed-age intervals, as in INE's methodology.

Usage

```
mean_age_at_childbearing(asfr_df)
```

Arguments

asfr_df	Output of <code>age_specific_fertility_rate()</code> .
---------	--

Value

A tibble with nuts3_code, province_name, year, mac (years).

Examples

```
asfr <- tibble::tibble(
  nuts3_code = "ES111", province_name = "A Coruna", year = 2023,
  age = c(20, 30), asfr = c(0.03, 0.08), asfr_female = c(0.015, 0.04)
)
mean_age_at_childbearing(asfr)
```

net_reproduction_rate *Net reproduction rate (NRR)*

Description

`sum(asfr_female * Lx / 10)`: expected daughters per woman allowing for the mother's survival, with Lx from the female period life table of the same province and year ([build_life_tables\(\)](#)'s `fltper`, radix 10 = 100000).

Usage

```
net_reproduction_rate(asfr_df, lt_df)
```

Arguments

`asfr_df` Output of [age_specific_fertility_rate\(\)](#).
`lt_df` [build_life_tables\(\)](#)'s `fltper` tibble (columns `nuts3_code`, `year`, `age`, `Lx`).

Value

A tibble with `nuts3_code`, `province_name`, `year`, `nrr`.

Examples

```
asfr <- tibble::tibble(
  nuts3_code = "ES111", province_name = "A Coruna", year = 2023,
  age = c(20, 30), asfr = c(0.03, 0.08), asfr_female = c(0.015, 0.04)
)
fltper <- tibble::tibble(
  nuts3_code = "ES111", year = 2023, age = c(20, 30), Lx = c(99000, 98500)
)
net_reproduction_rate(asfr, fltper)
```

plot_demog_trend	<i>Plot a demographic indicator trend over time</i>
------------------	---

Description

Generic time-series line chart for any indicator tibble keyed by nuts3_code/province_name/year, such as the output of [age_dependency_ratio\(\)](#), [aging_index\(\)](#), [sex_ratio\(\)](#), [crude_birth_rate\(\)](#), or [life_expectancy_summary\(\)](#).

Usage

```
plot_demog_trend(df, value_col, region = NULL, title = NULL, ylab = NULL)
```

Arguments

df	A tibble with province_name, year, and value_col.
value_col	Character, the name of the column to plot.
region	Optional character vector to subset by province name (regular expressions allowed, matched against province_name); one line is drawn per matched province. If NULL (default), every province present in df is plotted.
title	Optional plot title.
ylab	Optional y-axis label (defaults to value_col).

Value

A ggplot object.

Examples

```
trend <- tibble::tibble(
  nuts3_code = "ES111", province_name = "A Coruna",
  year = c(2022, 2023), aging_index = c(150, 160)
)
plot_demog_trend(trend, "aging_index")
```

plot_ine_map	<i>Plot a Map of Spain with Regions Highlighted</i>
--------------	---

Description

Plots the full map of Spain at the requested geographic level (provinces or municipalities), with one or more regions highlighted in a different color. Useful for confirming *which* regions a region filter passed to [get_ine_demog\(\)](#) or [get_ine_geo\(\)](#) actually matches, since [get_ine_geo\(\)](#) uses regex substring matching by default (see vignette examples in test_cordoba.R).

Usage

```
plot_ine_map(
  geo_level = c("province", "municipality"),
  highlight = NULL,
  base_color = "grey90",
  highlight_color = "firebrick",
  title = NULL,
  can_box = TRUE,
  can_gap_km = 60
)
```

Arguments

geo_level	Character, one of "province" or "municipality".
highlight	Character vector of region names to highlight (regular expressions allowed, matched against the geography name — same matching rules as <code>region</code> in get_ine_demog() / get_ine_geo()). If NULL (default), the whole map is plotted in <code>base_color</code> with no highlighting.
base_color	Fill color for non-highlighted regions. Default "grey90".
highlight_color	Fill color for highlighted regions. Default "firebrick".
title	Optional plot title.
can_box	Logical, draw an inset separator box around the Canary Islands, which are shifted next to the mainland for a compact map (default TRUE).
can_gap_km	Numeric, how close (in km) the shifted Canary Islands sit next to the mainland (default 60). Smaller values move them closer. See get_ine_geo() .

Value

A ggplot object.

Examples

```
## Not run:
# Not run: get_ine_geo() requires live network access to fetch boundaries.
plot_ine_map(geo_level = "province", highlight = "^Córdoba$")
plot_ine_map(geo_level = "municipality", highlight = "Córdoba")

## End(Not run)
```

plot_lexis_diagram	<i>Calculate and plot a Lexis diagram for one province</i>
--------------------	--

Description

Builds the classic demographic Lexis surface — age (y-axis) by calendar year (x-axis), shaded by mortality rate, with birth-cohort diagonals overlaid — for one province, from the age x year central death rates already computed by `compute_death_rates()`. Operates on data already retrieved/computed via the mortality pipeline (`get_ine_deaths()` -> `compute_exposure()` -> `compute_death_rates()`); it does not fetch anything itself.

Usage

```
plot_lexis_diagram(
  mx_df,
  province,
  sex = c("total", "female", "male"),
  log_scale = TRUE,
  rate_per = 1000,
  cohort_lines = TRUE,
  cohort_step = 10,
  title = NULL
)
```

Arguments

<code>mx_df</code>	Output of the <code>mx_1x1</code> element of <code>compute_death_rates()</code> (columns <code>nuts3_code</code> , <code>province_name</code> , <code>year</code> , <code>age</code> , <code>mx_female</code> , <code>mx_male</code> , <code>mx_total</code>).
<code>province</code>	Character, a province name (regular expressions allowed, matched against <code>province_name</code> — same convention as <code>region</code> in <code>plot_population_pyramid()</code>). Must match exactly one province.
<code>sex</code>	Character, one of "total", "female", "male".
<code>log_scale</code>	Logical (default TRUE), color-scale mortality rates on a log10 scale — the standard convention for Lexis surfaces, since <code>mx</code> spans several orders of magnitude across ages.
<code>rate_per</code>	Numeric, express the mortality rate as deaths per this many people (default 1000, the standard demographic convention — e.g. a legend value of 10 reads as "10 deaths per 1,000 population"). Use 1 for the raw per-person rate.
<code>cohort_lines</code>	Logical (default TRUE), overlay birth-cohort diagonals (<code>age = year - cohort</code>).
<code>cohort_step</code>	Numeric, spacing in years between overlaid cohort diagonals (default 10).
<code>title</code>	Optional plot title (defaults to the matched province name).

Details

"Calculate" here means deriving the tidy age x year surface for the requested province/sex and the cohort-diagonal positions to overlay ($\text{age} = \text{year} - \text{cohort}$, for cohorts every `cohort_step` years across the data's range) — not fitting a new mortality model; the rates themselves come straight from `compute_death_rates()`.

The white diagonal lines are intentional, not an artifact. They are birth-cohort lines ($\text{age} = \text{year} - \text{cohort}$): every point along one line represents the same group of people born in the same year, aging one year for every calendar year that passes — the defining feature of a Lexis diagram, letting you trace one cohort's mortality experience across its lifetime instead of only reading across a fixed year or up a fixed age. Set `cohort_lines = FALSE` to turn them off.

Grey cells mean no rate could be computed for that age x year cell, almost always because the source population data has no single-year age breakdown for the oldest ages in the earliest years of the series (so exposure, the rate's denominator, is missing there) — not a bug in the calculation. This typically shows up as a rectangular block in the upper-left (oldest ages, earliest years), clearing up once the source data's age detail becomes complete. When present, grey gets its own "Missing data" legend key (a continuous color scale can't show this on its own, so it's added via a small dummy layer).

Value

A ggplot object.

Examples

```
mx <- tibble::tibble(
  nuts3_code = "ES111", province_name = "A Coruna",
  year = rep(2020:2023, each = 3), age = rep(c(0, 50, 90), 4),
  mx_total = c(
    0.004, 0.003, 0.15, 0.0038, 0.0031, 0.14,
    0.0035, 0.0029, 0.16, 0.0033, 0.0028, 0.15
  )
)
plot_lexis_diagram(mx, province = "A Coruna")
```

plot_population_pyramid

Plot a population pyramid

Description

Draws a population pyramid for one province and year from age-disaggregated population data. Requires an age/sex breakdown, so it operates on `get_ine_population()`'s output, not `get_ine_demog()`'s `population_total` indicator.

Usage

```
plot_population_pyramid(pop_df, year, region = NULL, title = NULL)
```

Arguments

pop_df	Population tibble as returned by <code>get_ine_population()</code> \$data (columns province_name, year, age, female, male).
year	Numeric, the year to plot.
region	Optional character vector to subset by province name (regular expressions allowed, matched against province_name). If more than one province matches, counts are summed across them. If NULL (default), all provinces are summed (national pyramid).
title	Optional plot title.

Value

A ggplot object.

Examples

```
pop <- tibble::tibble(
  province_name = "A Coruna", year = 2023,
  age = c(0, 1), female = c(100, 90), male = c(105, 95)
)
plot_population_pyramid(pop, year = 2023)
```

rate_of_natural_increase

Rate of natural increase

Description

Computes the rate of natural increase ($RNI = CBR - CDR$, per 1,000 population) per province and year, combining already-computed [crude_birth_rate\(\)](#) and [crude_death_rate\(\)](#) output rather than re-deriving from raw births/deaths/population — consistent with how [life_expectancy_summary\(\)](#) consumes [build_life_tables\(\)](#)'s output rather than recomputing it.

Usage

```
rate_of_natural_increase(cbr_df, cdr_df)
```

Arguments

cbr_df	Output of crude_birth_rate() (columns nuts3_code, province_name, year, cbr).
cdr_df	Output of crude_death_rate() (columns nuts3_code, year, cdr).

Value

A tibble with nuts3_code, province_name, year, rni. A positive value means births outnumber deaths (population growing from natural change alone, ignoring migration); negative means the reverse.

Examples

```
cbr <- tibble::tibble(
  nuts3_code = "ES111", province_name = "A Coruna", year = 2023, cbr = 6.5
)
cdr <- tibble::tibble(nuts3_code = "ES111", year = 2023, cdr = 12.3)
rate_of_natural_increase(cbr, cdr)
```

sex_ratio	<i>Sex ratio</i>
-----------	------------------

Description

Computes the sex ratio (males per 100 females) per province and year from age-disaggregated population data. Requires the female/male columns `get_ine_population()` provides; `get_ine_demog()`'s `population_total` indicator has no sex breakdown and cannot be used here.

Usage

```
sex_ratio(pop_df, by_age = FALSE)
```

Arguments

- `pop_df` Population tibble as returned by `get_ine_population()`\$data (columns `nuts3_code`, `province_name`, `year`, `age`, `female`, `male`).
- `by_age` Logical, keep the age column and compute a sex ratio per age (default FALSE, which aggregates over all ages first).

Value

A tibble with `nuts3_code`, `province_name`, `year` (and `age` if `by_age = TRUE`), `sex_ratio`.

Examples

```
pop <- tibble::tibble(
  nuts3_code = "ES111", province_name = "A Coruna", year = 2023,
  age = c(0, 1), female = c(100, 95), male = c(105, 100)
)
sex_ratio(pop)
sex_ratio(pop, by_age = TRUE)
```

total_fertility_rate	<i>Total fertility rate (TFR)</i>
----------------------	-----------------------------------

Description

Sum of [age_specific_fertility_rate\(\)](#)'s asfr (births per woman) over single years of age: the expected number of children per woman under the year's age schedule.

Usage

```
total_fertility_rate(asfr_df)
```

Arguments

asfr_df Output of [age_specific_fertility_rate\(\)](#).

Value

A tibble with nuts3_code, province_name, year, tfr (children per woman).

Examples

```
asfr <- tibble::tibble(
  nuts3_code = "ES111", province_name = "A Coruna", year = 2023,
  age = c(20, 30), asfr = c(0.03, 0.08), asfr_female = c(0.015, 0.04)
)
total_fertility_rate(asfr)
```

update_ine_data	<i>Update INE Data</i>
-----------------	------------------------

Description

Checks each indicator wired in [ine_variables](#) for its latest published year (via [get_ine_demog\(\)](#)) and, if newer than the local cache, downloads and caches it for offline use.

Usage

```
update_ine_data(force = FALSE, data_dir)
```

Arguments

force Logical, force update even if data is current.

data_dir Character, directory for cached data. No default: this function only writes when a directory is explicitly supplied, per CRAN policy against writing to the user's home filespace by default. Pass e.g. `tools::R_user_dir("inedemogR", "cache")` for a persistent cache.

Value

Invisibly, a named list of the latest cached year per indicator.

Examples

```
## Not run:
# Not run: requires live network access to the INE API, and writes to
# the supplied cache directory.
update_ine_data(data_dir = tools::R_user_dir("inedemogR", "cache"))

## End(Not run)
```

validate_abridged_life_table

Validate a constructed abridged life table

Description

Fails when any column is missing or non-finite, $1x$ increases, Lx or ex is not positive, qx lies outside $[0, 1]$, or the identity $mx = dx / Lx$ fails in a closed interval from age 5 upward (the 0-4 group is built from single-year rates, so its grouped mx need not satisfy it exactly).

Usage

```
validate_abridged_life_table(alt)
```

Arguments

`alt` Output of `build_abridged_life_table()` for one year.

Value

`list(passed = logical, issues = named list of flagged tibbles).`

Examples

```
mx1 <- data.frame(age = 0:4, mx = c(0.004, 0.0003, 0.0002, 0.0002, 0.0002))
mx5 <- data.frame(
  age_group = c("00-04", "05-09", "100+"), mx = c(0.0006, 0.0001, 0.35)
)
alt <- build_abridged_life_table(mx1, mx5, "female")
validate_abridged_life_table(alt)
```

validate_births	<i>Validate cleaned provincial birth data</i>
-----------------	---

Description

Checks: sex ratio at birth (SRB) implausibly far from the expected value, accounting for sample size; no negative/missing counts; no duplicate province-year rows; continuous year coverage.

Usage

```
validate_births(df)
```

Arguments

df Output of the data element of `get_ine_births()`.

Details

The SRB check does not use a single fixed band (an earlier version used [1.030, 1.070], which flagged ~60% of all province-years, including 38% of Madrid/Barcelona's — clearly miscalibrated: annual province-level SRB is naturally noisy for small birth counts, and this data's own pooled SRB runs about 1.06, already above that band's upper bound even before any noise). Instead it flags a province-year only if *both* (a) the observed SRB is statistically implausible given that year's birth count, assuming a true underlying SRB of 1.06 (a two-tailed z-test on the male-birth proportion at $z > 4$, i.e. roughly a 1-in-16,000 event under the null - deliberately strict, since thousands of province-years are tested at once), and (b) the deviation is also practically meaningful (SRB more than 0.03 from 1.06), so statistically-significant-but-tiny deviations in large provinces aren't flagged just because their sample size makes the test hyper-sensitive. An SRB outside [0.90, 1.25] is additionally always flagged as a sanity floor for gross data errors, but only once total births reach 200: below that, even a large swing (e.g. 23 vs. 17 births) is unremarkable binomial noise, not a data problem, and the z-test above already accounts for the small sample correctly.

Value

list(passed = logical, issues = named list of flagged tibbles).

Examples

```
births_df <- tibble::tibble(
  nuts3_code = c("ES611", "ES611", "ES612", "ES612"),
  province_name = c("Almeria", "Almeria", "Cadiz", "Cadiz"),
  year = c(2020, 2021, 2020, 2021),
  female = c(950, 970, 1200, 1210),
  male = c(1000, 1020, 1260, 1270),
  total = female + male
)
validate_births(births_df)
```

 validate_births_by_age

Validate cleaned age-of-mother birth data

Description

Checks: no negative/missing counts; no duplicate province-year-age rows; single-year ages (15-49) present for every province-year found in the data (the two open intervals, under15/50plus, are not required to be present since they are typically very small or zero).

Usage

```
validate_births_by_age(df)
```

Arguments

df Output of the data element of `get_ine_births_by_age()`.

Value

list(passed = logical, issues = named list of flagged tibbles).

Examples

```
# Only 3 of the 35 required single-year ages (15-49) are present here,
# so this deliberately triggers the incomplete age coverage check.
births_age_df <- tibble::tibble(
  nuts3_code = "ES611",
  province_name = "Almeria",
  year = 2020,
  age = c(20, 21, 22),
  age_group = c("20", "21", "22"),
  female = c(30, 28, 25),
  male = c(32, 29, 27),
  total = female + male
)
validate_births_by_age(births_age_df)
```

 validate_deaths

Validate cleaned provincial death data

Description

Checks: sex ratio at death in [0.90, 1.50]; no negative/missing counts; no duplicate province-year rows; continuous year coverage; provincial sum vs. national total (if nat_df supplied).

Usage

```
validate_deaths(prov_df, nat_df = tibble::tibble())
```

Arguments

prov_df Province-level cleaned deaths tibble.
 nat_df National-level cleaned deaths tibble (optional).

Value

list(passed = logical, issues = named list of flagged tibbles).

Examples

```
deaths_df <- tibble::tibble(
  nuts3_code = c("ES611", "ES611", "ES612", "ES612"),
  province_name = c("Almeria", "Almeria", "Cadiz", "Cadiz"),
  year = c(2020, 2021, 2020, 2021),
  female = c(480, 500, 610, 630),
  male = c(510, 520, 640, 655),
  total = female + male
)
validate_deaths(deaths_df)
```

validate_deaths_age	<i>Validate cleaned age-specific provincial death data</i>
---------------------	--

Description

Checks: no negative/missing counts; no duplicate province-age-year rows; continuous year coverage per province.

Usage

```
validate_deaths_age(df)
```

Arguments

df Age-specific province deaths tibble.

Value

list(passed = logical, issues = named list of flagged tibbles).

Examples

```
deaths_age_df <- tibble::tibble(
  nuts3_code = c("ES611", "ES611"),
  province_name = c("Almeria", "Almeria"),
  year = c(2020, 2020),
  age = c(0, 1),
  female = c(2, 0),
  male = c(3, 1),
  total = female + male
)
validate_deaths_age(deaths_age_df)
```

validate_death_rates	<i>Validate computed central death rates</i>
----------------------	--

Description

Fails on negative, missing, or infinite rates; on rates ≥ 1 below age 90; and on any province-year without unique, complete single ages 0-100.

Usage

```
validate_death_rates(mx_df)
```

Arguments

`mx_df` Output of the `mx_1x1` element of `compute_death_rates()`.

Value

`list(passed = logical, issues = named list of flagged tibbles).`

Examples

```
deaths <- tibble::tibble(
  nuts3_code = "ES111", province_name = "A Coruna", year = 2023,
  age = c(0, 1), female = c(1, 0), male = c(1, 1), total = c(2, 1)
)
exposure <- tibble::tibble(
  nuts3_code = "ES111", province_name = "A Coruna", year = 2023,
  age = c(0, 1), female = c(500, 490), male = c(510, 505), total = c(1010, 995)
)
rates <- compute_death_rates(deaths, exposure)
validate_death_rates(rates$mx_1x1)
```

validate_exposure	<i>Validate computed exposure-to-risk values</i>
-------------------	--

Description

Checks: cells with no usable source population (flagged for audit, not treated as an error); no other negative/NA exposures; exposure should not exceed 2x population (a generous plausibility bound).

Usage

```
validate_exposure(exposure_df, population_df)
```

Arguments

exposure_df Output of the data element of `compute_exposure()`.
 population_df The population tibble originally passed in.

Value

list(passed = logical, issues = named list of flagged tibbles).

Examples

```
exposure_df <- tibble::tibble(
  nuts3_code = "ES611", year = 2020, age = c(0, 1),
  female = c(495, 480), male = c(520, 500), total = c(1015, 980),
  is_boundary_year = FALSE, is_missing_source_pop = FALSE
)
population_df <- tibble::tibble(
  nuts3_code = "ES611", year = 2020, age = c(0, 1), total = c(1000, 970)
)
validate_exposure(exposure_df, population_df)
```

validate_life_table	<i>Validate a constructed life table</i>
---------------------	--

Description

Fails when any of the following holds: ages are not unique and contiguous from 0; any of mx, qx, ax, lx, dx, Lx, Tx, ex is missing or non-finite; lx increases with age; Lx or ex is not positive; qx lies outside [0, 1]; mx = dx/Lx does not hold; or life expectancy at birth is outside the plausibility band (15, 100] years.

Usage

```
validate_life_table(lt)
```

Arguments

`lt` Output of `build_life_table()` for one year and sex.

Value

`list(passed = logical, issues = named list).`

Examples

```
mx <- data.frame(age = 0:100, mx = 0.0003 * exp(0.07 * (0:100)))
validate_life_table(build_life_table(mx, "female"))
```

validate_population	<i>Validate cleaned provincial population data</i>
---------------------	--

Description

Checks: no negative/missing counts; full age range (0..100) present per province-year; no duplicate province-age-year rows; continuous year coverage; no implausible age-to-age jumps (>50%, informational only).

Usage

```
validate_population(df)
```

Arguments

`df` Output of the data element of `get_in_e_population()`.

Value

`list(passed = logical, issues = named list of flagged tibbles).`

Examples

```
population_df <- tibble::tibble(
  nuts3_code = c("ES611", "ES611"),
  province_name = c("Almeria", "Almeria"),
  year = c(2020, 2020),
  age = c(0, 1),
  female = c(480, 490),
  male = c(500, 505),
  total = female + male
)
validate_population(population_df)
```

Index

* datasets

ine_variables, 27

age_dependency_ratio, 3
age_dependency_ratio(), 7, 35
age_specific_fertility_rate, 4
age_specific_fertility_rate(), 14, 18, 20, 26, 33, 34, 41
aging_index, 5
aging_index(), 7, 35
andreev_kingkade_a0, 6
andreev_kingkade_a0(), 8

birth_death_ratio, 7
build_abridged_life_table, 7
build_abridged_life_table(), 8, 42
build_abridged_life_tables, 8
build_life_table, 9
build_life_table(), 8, 16, 28, 48
build_life_tables, 10
build_life_tables(), 7–9, 12, 16, 29, 30, 32, 34, 39

compute_death_rates, 11
compute_death_rates(), 8–10, 21, 29, 37, 38, 46
compute_exposure, 13
compute_exposure(), 11, 12, 21, 47
crude_birth_rate, 14
crude_birth_rate(), 15, 18, 35, 39
crude_death_rate, 15
crude_death_rate(), 28, 39

decompose_life_expectancy, 15
download_ine_data, 17
download_ine_data(), 19

general_fertility_rate, 18
get_ine_births, 19
get_ine_births(), 14, 18, 20, 21, 28, 43
get_ine_births_by_age, 20
get_ine_births_by_age(), 14, 18, 44
get_ine_deaths, 21
get_ine_deaths(), 12, 13, 15, 28
get_ine_demog, 23
get_ine_demog(), 3, 5, 7, 19, 24, 31, 35, 36, 38, 40, 41
get_ine_geo, 24
get_ine_geo(), 23, 30–33, 35, 36
get_ine_population, 25
get_ine_population(), 3, 5, 7, 13–15, 18, 38, 40, 48
gross_reproduction_rate, 26
gross_reproduction_rate(), 4, 20

ine_variables, 23, 27, 41
ineapir::get_data_table(), 23, 27
infant_mortality_rate, 28

life_expectancy, 29
life_expectancy(), 16
life_expectancy_summary, 30
life_expectancy_summary(), 16, 29, 32, 33, 35, 39
list_ine_indicators, 30
list_ine_indicators(), 23

map_indicator, 31
map_indicator(), 32
map_life_expectancy, 32
map_life_expectancy(), 30, 31
mean_age_at_childbearing, 33
mean_age_at_childbearing(), 20

net_reproduction_rate, 34
net_reproduction_rate(), 4, 20

plot_demog_trend, 35
plot_ine_map, 35
plot_ine_map(), 24, 32
plot_lexis_diagram, 37
plot_lexis_diagram(), 29

plot_population_pyramid, [38](#)
plot_population_pyramid(), [37](#)

rate_of_natural_increase, [39](#)
rate_of_natural_increase(), [15](#)

sex_ratio, [40](#)
sex_ratio(), [7](#), [35](#)

total_fertility_rate, [41](#)
total_fertility_rate(), [14](#), [18](#), [20](#)

update_in_data, [41](#)

validate_abridged_life_table, [42](#)
validate_abridged_life_table(), [9](#)
validate_births, [43](#)
validate_births(), [20](#)
validate_births_by_age, [44](#)
validate_births_by_age(), [21](#)
validate_death_rates, [46](#)
validate_death_rates(), [12](#)
validate_deaths, [44](#)
validate_deaths_age, [45](#)
validate_exposure, [47](#)
validate_exposure(), [13](#)
validate_life_table, [47](#)
validate_population, [48](#)
validate_population(), [26](#)